



## **BSI Standards Publication**

### **Wall and floor tiling**

Part 3: Design and installation of internal and external ceramic and mosaic, natural stone and terrazzo flooring, and internal agglomerated stone flooring in normal conditions – Code of practice

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2024

Published by BSI Standards Limited 2024

ISBN 978 0 539 19927 7

ICS 91.060.10; 91.060.30

The following BSI references relate to the work on this document:

Committee reference B/539

Draft for comment 23/30446311 DC

**Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

Contents		Page
	Foreword	IX
Section 1	General	1
1	Scope	1
2	Normative references	1
3	Terms and definitions	3
	Figure 1 — Illustration of selected definitions – Ceramic tile installation	3
	Figure 2 — Illustration of selected definitions – Natural stone/terrazzo installation	4
4	Exchange of information and time schedule	8
4.1	Exchange of information	8
4.2	Provision of utilities, facilities and materials	9
4.3	Time schedule	9
5	Materials – Transport and storage	10
5.1	Delivery to site and unloading	10
5.2	Storage	11
5.3	Distribution	11
6	Bedding and levelling screeds	11
6.1	Cement	11
6.2	Separating layers	14
Section 2	Ceramic tiles	25
7	Ceramic	25
7.1	General	25
7.2	Thin ceramic tiles and panels (non-mesh backed)	25
	Figure 3 — Example of correct handling of large ceramic panels	27
8	Inspection	28
9	Protection	28
9.1	General	28
9.2	Grouts for tile joints	29
9.3	Sealants and back-up materials for movement joints	29
9.4	Substrates	30
	Table 1 — Suitability of tile beds for different substrates	31
9.5	Durability and performance	39
	Table 2 — Grouts and joint materials: stain resistance to intermittent contact with various liquids and characteristics	43
9.6	Passage of liquids through floors	43
9.7	Variations in moisture content and temperature	44
9.8	Isolation of tile bed from the substrate	45
9.9	Movement joints	45
	Figure 4 — Typical movement joints – Slightly flexible joint: preformed strip with reinforced edges	47
	Figure 5 — Typical movement joints – Prefabricated joint with reinforced edges and capping over structural movement joint	48
	Figure 6 — Typical movement joints – Flexible joint in bed, with or without separating layer	49
	Figure 7 — Typical movement joints – Joint aligned to structural movement joint	50
	Figure 8 — Typical movement joints – Perimeter joints (with skirtings)	51
	Figure 9 — Typical movement joints – Alternative perimeter joints (with skirting)	51
	Figure 10 — Intermediate movement joint profile – PVC anchoring legs	53
	Figure 11 — Intermediate movement joint profile – Metal anchoring legs	54
	Figure 12 — Perimeter/connection movement joint profile	56

	<i>Figure 13 — Typical edge protection and transition profiles</i>	57
	<i>Figure 14 — Typical stair nosing profile</i>	58
9.10	Modular installations	61
9.11	Skirtings	62
9.12	Selection of bedding methods, grouts and joint materials	62
10	Application of ceramic tiles and slabs – Methods and materials	62
10.1	General	62
10.2	Bedding methods	65
10.3	Grouting	67
11	Cleaning and maintenance	68
11.1	General	68
11.2	Residual grout film	69
11.3	Efflorescence	70
11.4	Temporary tile sealers	70
11.5	Cleaning and slip resistance	70
11.6	Cleaning agents	71
<b>Section 3</b>	<b>Stone</b>	<b>73</b>
12	Natural stone for internal and external flooring	73
12.1	General	73
12.2	Joints in natural stone tiles and slabs	74
12.3	Stone samples and testing	74
	<i>Table 3 — Maximum recommended size for tiles and slabs set on an adhesive bed</i>	75
	<i>Table 4 — PCT of characteristics stone for tiles and slabs</i>	76
12.4	Impregnating sealers, surface sealers and waxes	78
12.5	Movement joints	80
	<i>Figure 15 — Stone on a semi-dry bed – Perimeter joint below skirting</i>	81
	<i>Figure 16 — Example of movement joints in screed perimeter</i>	82
	<i>Figure 17 — Semi-dry bed – Intermediate movement joint</i>	84
	<i>Figure 18 — Flexible silicone movement joint – Stone tiles or slabs on an adhesive bed</i>	85
	<i>Figure 19 — Intermediate silicone movement joints stone slabs on a semi-dry bed</i>	85
	<i>Figure 20 — Semi-dry bed – Interface junctions</i>	86
	<i>Figure 21 — Intermediate joint – Stone floor with underfloor heating</i>	86
12.6	Ground supported floor slabs with fully bonded stone finish	87
12.7	Ground supported floor slabs with de-bonded stone finish	87
12.8	Suspended floor slabs with stone finish	87
	<i>Figure 22 — Semi-dry bed – Structural movement joint</i>	87
12.9	Special circumstances	88
12.10	Location of movement joints	88
13	Installation of natural stone tiles and slabs	88
13.1	Bedding in adhesive	88
13.2	Bedding in cement:sand semi-dry mix	88
13.3	Grouting	89
13.4	Protection during construction	90
13.5	Cleaning and maintenance	91

<b>Section 4</b>	<b>Agglomerated stone</b>	<b>93</b>
14	Installation of agglomerated stone	93
14.1	General	93
14.2	Moisture sensitivity	93
14.3	Thermal movement	93
14.4	Bedding methods	94
14.5	Grouting	94
14.6	Sealing	94
14.7	Movement joints	95
15	Cleaning and maintenance	95
15.1	General	95
15.2	Installation/builder's clean	96
15.3	Daily/weekly maintenance	96
15.4	Deep cleaning	96
<b>Section 5</b>	<b>Terrazzo</b>	<b>97</b>
16	Terrazzo	97
16.1	Protection during construction	97
16.2	Storage and transportation	98
16.3	Impregnating sealers, surface sealers and waxes	99
17	Design	100
17.1	General	100
17.2	Finished floor level	100
17.3	Load considerations	101
17.4	Terrazzo tiles and slabs for internal and external floorings	103
18	Terrazzo tile and slab flooring	106
18.1	Bedding methods	106
18.2	Beds	106
18.3	Movement joints	106
	<i>Figure 23 — Alternative perimeter joints for terrazzo tile and slab flooring</i>	107
	<i>Figure 24 — Semi-dry bed – Structural movement joint</i>	110
18.4	Application of terrazzo tiles and slabs	110
18.5	Grouting	112
18.6	Grinding and polishing	113
18.7	Cleaning	114
<b>Section 6</b>	<b>Mosaic</b>	<b>116</b>
19	Mosaic tiles	116
19.1	General	116
19.2	Application of mosaics – Methods and materials	116
19.3	Workmanship	117
19.4	Mosaic beds	117
19.5	Setting out	118
19.6	Tolerances on finished floor level	118
19.7	Movement joints	119
19.8	Preparation of mosaics	119
19.9	Laying mosaics	119
19.10	Grouting	120

<b>Annex A</b>	<b>(normative) Ceramic tile fittings</b>	<b>121</b>
	<i>Figure A.1 — Battiscopa skirting</i>	121
	<i>Figure A.2 — Sit-on cove systems – Dry pressed tiles</i>	122
	<i>Figure A.3 — Flushfit cove systems – Dry pressed tiles</i>	122
	<i>Figure A.4 — Flushfit cove systems – Dry pressed tiles</i>	122
	<i>Figure A.5 — Typical floor channels – Extruded tiles</i>	123
	<i>Figure A.6 — Typical floor channels – Dry pressed tiles</i>	123
	<i>Figure A.7 — Typical step treads – Dry pressed tiles</i>	123
	<i>Figure A.8 — Typical step tread – Dry pressed tiles (large format)</i>	124
<b>Annex B</b>	<b>(informative) Special conditions included in BS 5385-4</b>	<b>124</b>
<b>Annex C</b>	<b>(normative) Tiling onto underfloor heated substrates</b>	<b>125</b>
C.1	Types of heating system	125
	<i>Figure C.1 — Type A heating system</i>	126
	<i>Figure C.2 — Type B heating system</i>	127
	<i>Figure C.3 — Type C heating system</i>	128
	<i>Figure C.4 — Type D heating system</i>	130
	<i>Figure C.5 — Type E heating system</i>	131
C.2	Design considerations	131
C.3	Hot water heated cement and sand screeds – Natural stone and terrazzo	133
C.4	Underfloor heating – Operating temperatures	134
	<i>Table C.1 — Maximum surface temperature</i>	134
C.5	Electric underfloor heating	134
C.6	Selection of hard flooring	134
C.7	Selection of adhesive and grout	136
<b>Annex D</b>	<b>(normative) Pumped calcium sulfate-based screeds</b>	<b>137</b>
D.1	General	137
	<i>Table D.1 — Application thicknesses for levelling screed</i>	137
D.2	Substrate information	138
D.3	Surface treatment	138
D.4	Drying	138
	<i>Table D.2 — Sample drying times in ideal drying conditions</i>	139
D.5	Residual moisture levels	139
D.6	Product recognition	139
D.7	Joints in screed	139
D.8	Priming and levelling	140
D.9	Adhesive selection	140
D.10	Grout selection	140
<b>Annex E</b>	<b>(normative) Cement and sand levelling screeds conforming to BS 8204-1</b>	<b>141</b>
E.1	Design considerations	141
	<i>Table E.1 — Choice of in situ crushing resistance category for levelling screeds</i>	143
	<i>Table E.2 — Acceptance limits for in situ crushing resistance test</i>	143
	<i>Table E.3 — Classification of surface regularity [SR] of direct finished substrate slab or levelling screed</i>	144
E.2	Work on site	146
E.3	Inspection and testing of substrates and screeds	149

<b>Annex F</b>	<b>(normative) Method for the assessment of levels and surface regularity of levelling screeds</b>	<b>151</b>
	<i>Figure F.1 — Slip gauges for checking surface regularity</i>	151
<b>Annex G</b>	<b>(normative) Cement and sand bedding</b>	<b>152</b>
G.1	Cement for cement and sand mortar beds	152
G.2	Sand for cement and sand mortar beds	152
G.3	Admixtures to cement and sand mortars	152
G.4	Surface finish of the substrate	152
G.5	Semi-dry mix	152
G.6	Bedding in semi-dry cement and sand mix	153
G.7	Application of semi-dry mix (bonded method)	153
G.8	Separating layer (unbonded method)	153
G.9	Application of tiles	154
G.10	Bedding in cement and sand mortar bonded to a substrate	154
G.11	Preparation of porous tiles	155
G.12	Application of tiles	156
G.13	Movement joints	156
G.14	Tile bed thickness	156
	<i>Table G.1 — Thickness of tile bedding</i>	156
G.15	Cement and sand grout	156
G.16	Admixtures	157
G.17	Grouting with cement and sand mortar	157
<b>Annex H</b>	<b>(informative) Guidance on the reduction of slip hazard</b>	<b>157</b>
H.1	General	157
H.2	Design	158
H.3	In-service	159
H.4	Personal responsibility	160
	<b>Bibliography</b>	<b>161</b>

### Summary of pages

This document comprises a front cover, an inside front cover, pages I to X, pages 1 to 163, and a back cover.





---

# Foreword

## Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 May 2024. It was prepared by Technical Committee B/539, *Ceramic tiles and other rigid tiling*. A list of organizations represented on this committee can be obtained on request to the committee manager.

## Supersession

This part of BS 5385 supersedes [BS 5385-3:2014](#) and [BS 5385-5:2009](#), which are withdrawn.

## Relationship with other publications

This part of BS 5385 is one of a series dealing with the installation of floor and wall tiling the other parts being:

- Part 1: Design and installation of ceramic natural stone and mosaic wall tiling in normal internal conditions – Code of practice;
- Part 2: Design and installation of external ceramic and mosaic wall tiling in normal conditions – Code of practice; and
- Part 4: Design and installation of ceramic and mosaic tiling in special conditions – Code of practice.

## Information about this document

This is a full revision of the standard, and introduces the following principal changes:

- a) inclusion of natural stone, resin agglomerated stone and terrazzo;
- b) inclusion of calcium sulfate-based boards;
- c) recommendations on movement joints have been updated;
- d) inclusion of a subclause on steps, stairs and slopes (see [6.2.4](#));
- e) inclusion of a subclause on light reflectance values (see [6.2.5](#));
- f) inclusion of a subclause on the safe handling of materials (see [6.2.6](#));
- g) inclusion of slabs to pedestals; and
- h) updated recommendations on slip resistance.

**Assessed capability.** Users of this British Standard are advised to consider the desirability of quality system assessment and registration against the appropriate standard in the BS EN ISO 9000 series by an accredited third-party certification body.

This publication can be withdrawn, revised, partially superseded or superseded. Information regarding the status of this publication can be found in the Standards Catalogue on the BSI website at [knowledge.bsigroup.com](https://knowledge.bsigroup.com), or by contacting the Customer Services team.

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

## Hazard warnings

**WARNING:** This British Standard calls for the use of substances and/or procedures that can be injurious to health if adequate precautions are not taken. It refers only to technical suitability and does not absolve the user from legal obligations relating to health and safety at any stage.

## Use of this document

As a code of practice, this British Standard takes the form of recommendations and guidance. It is not to be quoted as if it were a specification. Users are expected to ensure that claims of compliance are not misleading.

Users may substitute any of the recommendations in this British Standard with practices of equivalent or better outcome. Any user claiming compliance with this British Standard is expected to be able to justify any course of action that deviates from its recommendations.

## Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is “should”.

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.*

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. “organization” rather than “organisation”).

## Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient’s own risk.

The recipient is advised to consider seeking professional guidance with respect to the use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

## Compliance with a British Standard cannot confer immunity from legal obligations.

Attention is drawn to the following statutory regulations:

- Building and Construction Regulations under the Factories Act 1961 [1];
- Lifting Operations and Lifting Equipment Regulations (LOLER) 1998 [2];
- Manual Handling Operations Regulations 1992 [3].

---

# Section 1 General

---

## 1 Scope

This part of BS 5385 specifies recommendations for the design, installation and maintenance of floor tiling using ceramic tiles, mosaic, terrazzo tile and slab and natural stone internal and external floorings, and agglomerated stone for internal flooring.

*NOTE 1* Tiles and slabs can be installed on concrete, cement and sand screed, calcium sulfate-based screeds, timber, flooring grade asphalt or existing hard floor finishes in normal conditions, using the methodology detailed in this British Standard. In addition, terrazzo and natural stone slabs can be laid on a cement:sand or mortar bed. For special conditions, see [BS 5385-4](#). Tile fittings for use as skirting, step treads and channels are given in [Annex A](#).

*NOTE 2* Stone tiles and slabs selected for use as external flooring laid only on an adhesive bed are limited to balconies, roof terraces and patios in residential applications. For all other external applications for natural stone flooring/paving, see [BS 7533-101](#).

*NOTE 3* Tiles and slabs can be installed on appropriate acoustic floors and pedestal systems.

*NOTE 4* Where the floor tiling installation needs to meet specific functional or environmental requirements, or to assist in counteracting potentially detrimental effects on the installation and/or the structure, see [BS 5385-4](#).

*NOTE 5* The special conditions described in [BS 5385-4](#), e.g. swimming pools, shower areas, etc. are given in [Annex B](#). [Annex C](#) specifies recommendations for tiling onto underfloor heated substrates and [Annex D](#) contains information on pumped calcium sulfate-based screeds. Recommendations for the design and laying of levelling screeds are given in [Annex E](#). Reference is made to tiles bedded directly to a concrete substrate, however for the design and construction of concrete substrates, see [BS 8204-1](#). [Annex F](#) contains a method for assessing levels and surface regularity and [Annex G](#) has guidance on cement and sand bedding. [Annex H](#) provides guidance on the reduction of slip hazards.

---

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes provisions of this document<sup>1)</sup>. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

### Standards publications

[BS 4483](#), *Steel fabric for the reinforcement of concrete – Specification*

[BS 4551](#), *Mortar – Methods of test for mortar – Chemical analysis and physical testing*

[BS 5385-4](#), *Wall and floor tiling – Part 4: Design and installation of ceramic and mosaic tiling in special conditions – Code of practice*

[BS 6100-0](#), *Building and civil engineering – Vocabulary – Part 0: Introduction and index*

[BS 6213](#), *Selection of construction sealants – Guide*

[BS 6925:1988](#), *Specification for mastic asphalt for building and civil engineering (limestone aggregate)*

[BS 8000-11](#), *Workmanship on building sites – Part 11: Internal and external wall and floor tiling – Ceramic and agglomerated stone tiles, natural stone and terrazzo tiles and slabs, and mosaics – Code of practice*<sup>2)</sup>

---

<sup>1)</sup> Documents that are referred to solely in an informative manner are listed in the Bibliography.

<sup>2)</sup> This document also gives informative references to [BS 8000-11:2011](#).