BS 7883:2019



**BSI Standards Publication** 

Personal fall protection equipment – Anchor systems – System design, installation and inspection – Code of practice



## Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2019

Published by BSI Standards Limited 2019

ISBN 978 0 580 94933 3

ICS 13.340.60

The following BSI references relate to the work on this document: Committee reference PH/5 Draft for comment 19/30345056 DC

#### Amendments/corrigenda issued since publication

Date Text affected

Conte	nts	Page		
	Foreword	v		
0	Introduction	1		
	Table 1 — Non-load-limiting anchor system options and codification in accordance with			
	BS 8610:2017, Table 1	1		
	Table 2 — Load-limiting anchor system options and codification in accordance with			
	BS 8610:2017, Table 2	2		
	Table 3 — Anchor devices in accordance with BS EN 795:2012 and PD CEN/TS 16415:2013	2		
	Section 1: General	3		
1	Scope	3		
2	Normative references	4		
3	Terms and definitions	4		
	Figure 1 — Examples of anchor systems	5		
	Figure 2 — Examples of type A non-load-limiting anchor systems	6		
	Figure 3 — Examples of type A davit-type anchor systems	7		
	Figure 4 — Example of a type A load-limiting anchor system	8		
	Figure 5 — Examples of type B anchor systems	9		
	Figure 6 — Example of a type C non-load-limiting anchor system	10		
	Figure 7 — Examples of type C load-limiting anchor systems	10		
	Figure 8 — Example of a type D anchor system	11		
	Figure 9 — Examples of type E anchor systems	11		
	Figure 10 — Example of an accompanied descent type rescue	17		
	Figure 11 — Example of rescue – remotely or self-operated – direct attachment systems	18		
	Figure 12 — Example of a remotely operated redirect attachment type rescue	19		
	Section 2: System design	23		
4	Preliminary information	23		
4.1	4.1 General			
4.2	4.2 PFPS system design			
4.3	4.3 PFPS project details			
4.4	Risk assessment	24		
5	Design considerations	24		
5.1	General	24		
5.2	Structural suitability	25		
	Figure 13 — Examples of calculations on loads applied to anchor devices, structural anchors and			
	the base material	27		
	Figure 14 — Examples of how loads are applied to a structure in the case of a handrail at			
	different angles of rigging	30		
5.3	Trial tests	30		
5.4	Maximum system rating, SR <sub>max</sub>	31		
5.5	Configuration	31		
5.6	Anti-pendulum anchor devices	31		
	Figure 15 — Example of angles on a rooftop PFPS using an anti-pendulum anchor device where			
	their use is unavoidable – plan view	32		
5.7	Obligations of the system designer	32		
5.8	Anchor system modification – system designer responsibilities	33		
5.9	Frequency, intensity of use and design life	33		
5.10	Accessible and hidden elements	33		
5.11	Environmental/climatic considerations and design life	34		
5.12	Structural anchor(s)	35		

5.13	Free fall distance, free space	35		
5.14	Personal fall protection equipment (PFPE) 3			
5.15	Positioning			
	Figure 16 — Examples of type C and type D anchor systems installed on roofs	37		
5.16	Rescue and recovery plan	38		
5.17	Inspection	39		
	Figure 17 — Examples of using packers to support reaction loads of test apparatus	39		
5.18	Limitations of use	39		
6	Design considerations – application	40		
6.1	General	40		
6.2	Application types	40		
	Figure 18 — Example of an anchor system using more than one structural anchor	42		
	Figure 19 — Example of a typical rope access rigging configuration and how the load is applied			
	to the anchor point(s) of each anchor system	43		
	Figure 20 — Example of the increase in loadings on a working line or anchor slings caused by an			
	increase in the angle of the Y hang	44		
	Figure 21 — Example of using additional anchor points to provide additional protection to the user	45		
	Figure 22 — Example of loads on deviation anchor devices at different angles	47		
	Figure 23 — Examples of rigging deviation anchor devices	48		
	Figure 24 — Examples of rigging of re-anchor devices	49		
	Figure 25 — Examples of aid climbing anchor devices used for aid climbing under a soffit	50		
	Figure 26 — Examples of work positioning configurations	51		
7	Design considerations – type specific	54		
7.1	General	54		
7.2	Type A anchor systems	54		
	Figure 27 — Permitted directions of loading for paired anchor devices	55		
7.3	Type B anchor systems	56		
7.4	Type C anchor systems 5			
7.5	Type D anchor systems	58		
7.6	Type E anchor systems	59		
8	Positioning	60		
8.1	Positioning – general	60		
	Figure 28 — Illustration of edge distance requirement for anchor devices set in narrow sections	61		
8.2	Positioning – application specific	63		
8.3	Positioning – Type specific	65		
9	System design specification	67		
10	Information to be supplied by the system designer to the installer and inspector	67		
	Section 3: Installation	68		
11	Installation	68		
11.1	General	68		
11.2	Additional installation recommendations for hidden elements	70		
11.3	Additional installation recommendations specific to type B and type E anchor devices	70		
11.4	Marking, signage and labelling	71		
11.5	Information to be provided following installation	74		
	Section 4: Inspection	77		
12	Inspection	77		
12.1	General 77			
12.2	Inspection and verification	78		
40 -	Table 4 — Examples of inspection criteria, including categories of inspection results	83		
12.3	Inspection report	89		

Annex A	(normative) Type A anchor systems – service loads and design loads based on BS	
	8610:2017 anchor types and applications of use	91
	Table A.1 — Service loads and design loads of type A non-load-limiting anchor systems	91
	Table A.2 — Service loads and design loads of type A load-limiting anchor systems	92
Annex B	(normative) Type C anchor systems – service loads and design loads based on BS	
	8610:2017 anchor types and applications of use	93
	Table B.1 — Service loads and design loads of type C non-load-limiting anchor systems	93
	Table B.2 — Service loads and design loads of Type C load-limiting anchor systems	93
Anney (	(normative) Type D anchor systems - service loads and design loads based on RS	
AIIICAU	8610:2017 anchor types and applications of use	94
	Table C 1 — Service loads and design loads of Type D non-load-limiting anchor systems	94
		71
Annex D	(normative) Calculation of trial test loads	96
	Figure D.1 — Example of eyebolt-type anchor systems where the service load might be applied in	
	shear, $F_s$ , tension, $F_t$ , or any angle in between	97
	Figure D.2 — Example of the direction of trial test loads, $T_{d}$ , equal to the design load,	
	perpendicular to the base material, for eyebolt-type anchor devices	98
	Figure D.3 — Detail for calculation of trial test load, $T_c$ , for the structural anchors of anchor	
	devices with base plates	99
Annex E	(informative) Calculation and application of proof test loads	100
	Table E.1 — Examples of anchor devices/systems to be proof load tested	101
	Figure E.1 — Examples of applying proof test loads, $P_{_{\rm f}}$ , in the direction of the service load	103
	Figure E.2 — Examples of applying proof test loads, $P_{f}$ , equal to the service load, perpendicular to	
	the base material	104
	Figure E.3 — Example of basis of calculation and applying proof test loads, $P_{c}$ , applied	
	perpendicular to the base material, in the case of anchor devices with base plates	105
	Figure E.4 — Example of applying the calculated proof test load equally between two	
	anchor points	107
	Figure E.5 — Examples of applying calculated proof test loads, $P_{\rm c}$ , to individual structural	
	anchors in the case of anchor devices with base plates	108
	Figure E.6 — Example of basis of calculation of the calculated proof test load, $P_c$ , applied directly	
	to each structural anchor perpendicular to the base material, in the case of anchor devices with	
	base plates	109
	Figure E.7 — Examples of applying proof test load, $P_{\rm f}$ , equivalent to the service load to each	
	anchor point individually	110
Annex F	(informative) <b>Examples of anchor systems and applications showing the range of</b>	
	movement and working area	111
	Figure F.1 — Example of a restraint PFPS comprising central anchor point with a fixed	
	length lanyard	111
	Figure F.2 — Example of a restraint PFPS comprising perimeter anchor system with a fixed	
	length lanyard	112
	Figure F.3 — Example of a restraint PFPS using anti-pendulum anchor devices and	
	adjustable lanyards	113
	Figure F.4 — Example of a fall arrest PFPS comprising central anchor point with a fall	
	arrest lanyard	114
Annex G	(informative) <b>Example of forms to be provided by the system designer to be completed</b>	
	by the installer or duty holder	115
Anno- II	(informative) Example of an increation report form	117
Annex H	(mormative) Example of an inspection report form	117

117

Table H.1 — Report of inspection of personal fall protection systems (including anchor devices/anchor systems and personal fall protection equipment)

Annex I	(normative) Pre-use inspection	118
Annex J	(normative) Reverse-engineering design check of hidden elements	120
Annex K	(normative) Test apparatus and procedures for trial and proof load testing	121
	Figure K.1 — Example of a test apparatus arrangement for load testing structural anchors and/	
	or anchor systems	122
	Figure K.2 — Test apparatus arrangements for various anchor systems with test loads applied	
	perpendicular to the base material	123
	Figure K.3 — Example of test apparatus arrangement for load testing wire rope swage	
	terminations	125
	Figure K.4 — Example of test apparatus arrangement for load testing davit arms	126
	Figure K.5 — Example of testing davit arms in full range of movement – plan view	128
	Bibliography	129

## Summary of pages

This document comprises a front cover, and inside front cover, pages i to vi, pages 1 to 130, an inside back cover and a back cover.

# Foreword

# **Publishing information**

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 30 November 2019. It was prepared by Technical Committee PH/5, *Personal Fall Protection*. A list of organizations represented on this committee can be obtained on request to its secretary.

## **Supersession**

BS 7883:2019 supersedes BS 7883:2005, which is withdrawn.

## **Relationship with other publications**

This British Standard is intended to complement BS 8610, BS EN 795, PD CEN/TS 16415 by recommending good practice as followed by competent practitioners for installing and maintaining products conforming to those standards.

## Information about this document

This British Standard provides information relating to anchor systems and recommendations for installation and use in conjunction with personal fall protection equipment for protection against falls from a height.

This revision of BS 7883 gives recommendations additional to those in the previous edition for system design, installation and inspection of anchor systems, including:

- a) the role of the system designer is introduced;
- b) applications and product types have been introduced, based on BS 8610;
- c) recommendations have been introduced for:
  - 1) documentation, including the system technical file;
  - 2) configurations in use, in particular rope access;
  - 3) positioning;
  - 4) proof test loads; and
  - 5) the inspection of previously installed anchor systems.

#### Use of this document

As a code of practice, this British Standard takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this British Standard is expected to be able to justify any course of action that deviates from its recommendations.

It has been assumed in the preparation of this British Standard that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

## **Presentational conventions**

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should". This British Standard includes examples which are illustrative and not a definitive list.

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.* 

## **Contractual and legal considerations**

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

## Compliance with a British Standard cannot confer immunity from legal obligations.

Particular attention is drawn to the following specific regulations:

- The Work at Height Regulations 2005 (as amended) [1].
- The Construction (Design and Management) Regulations 2015 (CDM) [2].
- The Lifting Operations and Lifting Equipment Regulations 1998 (LOLER) [3].
- The Provision and Use of Work Equipment Regulations 1998 (PUWER) [4].
- The Workplace (Health, Safety and Welfare) Regulations 1992 [5].

## 0 Introduction

The dangers of working at height are not always apparent. Engineered controls have to be devised to protect persons working at height against the effects of gravity, i.e. falls from a height. Anchor systems are an essential part of such controls.

This British Standard is intended to guide system designers, installers, inspectors, duty holders, rescuers and users of anchor systems for fall protection in their safe use and relates primarily to anchor systems conforming to BS 8610 (see <u>Table 1</u> and <u>Table 2</u>) and anchor devices conforming to BS EN 795 and PD CEN/TS 16415 (see <u>Table 3</u>).

For clarification, BS 8610 specifies the type testing of anchor systems comprising the anchor device, the structural anchor and the base material for the following applications (single and multi-user):

- a) restraint;
- b) fall arrest;
- c) rope access;
- d) work positioning;
- e) rescue; and
- f) evacuation.

The test requirements within BS EN 795 are restricted to single user, fall arrest only and do not necessarily cover the structural anchor(s) and/or base material.

NOTE PD CEN/TS 16415 specifies requirements for multiple users, fall arrest only.

Table 1 — Non-load-limiting anchor system options and codification in accordance with BS 8610:2017, Table 1

Туре	Application code	Application use
A – e.g. eyebolt <sup>A)</sup> /post	1	Restraint
	2	Fall arrest
	3	Rope access and work positioning
	4	Rescue – accompanied descent
	5	Rescue – remotely or self-operated – direct attachment
	6	Rescue – remotely operated – redirect attachment
	7	Evacuation
C – e.g. flexible	1	Restraint
horizontal anchor line		
	2	Fall arrest
	5	Rescue – remotely or self-operated – direct attachment
D – e.g. rigid horizontal	1	Restraint
anchor line		
	2	Fall arrest
	3	Rope access and work positioning
	4	Rescue – accompanied descent
	5	Rescue – remotely or self-operated – direct attachment
	6	Rescue – remotely operated – redirect attachment
	7	Evacuation

<sup>A)</sup> As an example of codification, an eyebolt for fall arrest – non-load-limiting would be type A2.

NOTE Class A1 anchor devices that conform to BS EN 795:1997 are not the same as type A1 anchor systems (for restraint) that conform to BS 8610.

Туре	Application code	Application use	Load-limiting
A – e.g. eyebolt <sup>A)</sup> /post	1	Restraint	L
	2	Fall arrest	L
	5	Rescue – remotely or self-operated –	L
		direct attachment	
C – e.g. flexible horizontal anchor line	1	Restraint	L
	2	Fall arrest	L
	5	Rescue – remotely or self-operated –	L
		direct attachment	

 Table 2 — Load-limiting anchor system options and codification in accordance with BS 8610:2017, Table 2

Table 3 — Anchor devices in accordance with BS EN 795:2012 and PD CEN/TS 16415:2013

Туре	Application code	Application use
A – e.g. eyebolt/post	—	Suitable for multiple applications as specified in the
		information supplied by the manufacturer
B – anchor device	—	Suitable for multiple applications as specified in the
without structural		information supplied by the manufacturer
anchor		
C – horizontal flexible	—	Suitable for multiple applications as specified in the
anchor line		information supplied by the manufacturer
D – horizontal rigid	—	Suitable for multiple applications as specified in the
anchor line		information supplied by the manufacturer
E – anchor device relying	—	Suitable for multiple applications as specified in the
on mass and friction		information supplied by the manufacturer

*NOTE 1* BS EN 795 and PD CEN/TS 16415 do not have a coding system for application and cover non-load-limiting and load-limiting anchor devices.

*NOTE 2* For clarification, BS EN 795 and PD CEN/TS 16415 cover only anchor devices and not the structural anchor or the base material.

# Section 1: General

## 1 Scope

This British Standard gives recommendations for the system design, installation, use, maintenance and inspection of anchor systems incorporating anchor devices conforming to BS EN 795, PD CEN/ TS 16415 and/or anchor systems conforming to BS 8610.

This British Standard also gives recommendations for the inspection of anchor systems installed prior to this edition of the British Standard.

NOTE 1 Anchor systems installed prior to this edition of the British Standard, but which have been inspected in accordance with <u>Section 4</u>, can only be certified as meeting the inspection recommendations of <u>Section 4</u>. The inspector can only claim that the anchor system conforms to the British Standard to which it was originally installed, e.g. "the anchor system was installed in accordance with BS 7883:2005 and the inspection has been carried out in accordance with BS 7883:2019, Section 4".

This British Standard is only applicable to anchor systems for the direct attachment of PFPE for use in the workplace.

This British Standard is not applicable to:

- a) the lifting of equipment;
- b) anchor points comprising holes formed in the base material for the direct attachment of personal fall protection equipment (PFPE), e.g. hole drilled through steel girder;
- c) anchor points formed by the welded attachment of bars or plates to steel structures for the direct attachment of the PFPE, e.g. loops of steel bar or flat plates incorporating a hole, welded to a steel structure, unless:
  - 1) such anchor points form part of a manufactured product which has been successfully tested in accordance with BS 8610; or
  - 2) the manufacturer, installer or inspector of such anchor points can demonstrate that the anchor point conforms to all relevant requirements of BS 8610, BS EN 795 or PD CEN/ TS 16415, in which case the documentation certifying conformity to BS 8610, BS EN 795 or PD CEN/TS 16415 becomes part of the documentation provided to the duty holder;
- d) anchor systems for attachment of collective protection systems, e.g. work positioning platforms and fall arrest nets; and
- e) personal fall protection systems (PFPS) and equipment for use in leisure activities or in professional and private sports activities.

This British Standard is intended for use by system designers, installers, inspectors and users of anchor systems, including other interested parties, e.g. architects and structural engineers, and those who are responsible for the design of safe access and egress on buildings and structures.

*NOTE 2* Advice on the selection, use and maintenance of PFPS and equipment for use in the workplace is given in BS 8437 and recommendations and guidance on the use of rope access methods for industrial purposes are given in BS 7985.