



BSI Standards Publication

Stationary source emissions – Mercury monitoring using sorbent traps

National foreword

This Published Document is the UK implementation of CEN/TS 17286:2019.

The UK participation in its preparation was entrusted to Technical Committee EH/2/1, Stationary source emission.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 580 52298 7

ICS 13.040.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 March 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CEN/TS 17286

March 2019

ICS 13.040.40

English Version

**Stationary source emissions - Mercury monitoring using
sorbent traps**

Émissions de sources fixes - Surveillance du mercure à
l'aide de pièges adsorbants

Emissionen aus stationären Quellen -
Quecksilbermonitoring mit Sorptionsfallen

This Technical Specification (CEN/TS) was approved by CEN on 9 December 2018 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	8
4 Symbols and abbreviations	9
5 Principle	11
6 Measuring equipment	11
6.1 Sorbent trap monitoring system equipment specifications	11
6.1.1 Monitoring system	11
6.1.2 Moisture removal device	13
6.1.3 Vacuum pump.....	13
6.1.4 Total sample volume measurement.....	13
6.1.5 Sample flow rate meter and controller	13
6.1.6 Temperature sensor	13
6.1.7 Absolute pressure sensor.....	14
6.1.8 Automatic controller.....	14
6.1.9 Sample preparation.....	14
6.1.10 Sample analysis equipment.....	14
6.1.11 Sorbent trap spiking system	14
7 Reagents and standards.....	15
8 Performance specification test procedure	15
8.1 Selection of monitoring site and initial sampling conditions	15
8.2 Pre-sampling spiking of sorbent traps.....	15
8.3 Field blanks	15
8.4 Pre-monitoring leak check	16
8.5 Determination of flue gas characteristics	16
8.6 Monitoring.....	16
8.6.1 System preparation and initial data recording.....	16
8.6.2 Flow rate control	16
8.6.3 Flue gas moisture determination	17
8.6.4 Essential operating data	17
8.6.5 Post-monitoring leak check.....	17
8.6.6 Sample recovery	18
8.6.7 Sample handling, storage, and transport	18
8.6.8 Sample custody	18
9 Quality assurance/quality control (QA/QC).....	18
10 Calibration and standardization.....	21
10.1 Gaseous and liquid standards.....	21
10.2 Gas flow meter calibration.....	21
10.2.1 General.....	21
10.2.2 Initial calibration	21
10.2.3 Initial calibration procedures	21
10.2.4 Initial calibration factor	22

10.2.5	Optional on-site calibration audit for mass flow meters	22
10.2.6	Ongoing quality control.....	22
11	Analytical performance criteria.....	22
11.1	General	22
11.2	Analytical matrix interference test	23
11.2.1	General	23
11.2.2	Analytical matrix interference test procedures	23
11.2.3	Analytical matrix interference test acceptance criteria.....	23
11.3	Determination of minimum sample mass	24
11.3.1	General	24
11.3.2	Determination of minimum calibration concentration or mass.....	24
11.3.3	Determination of minimum sample mass	24
11.3.4	Example determination of minimum sample mass for thermal desorption analysis	24
11.3.5	Example determination of Minimum Sample Mass for Acid Leachate/Digest Analysis	24
11.4	Hg ⁰ and HgCl ₂ analytical bias test (ABT)	25
11.4.1	General	25
11.4.2	Hg ⁰ and HgCl ₂ ABT procedures	25
11.4.3	Hg ⁰ ABT.....	25
11.4.4	HgCl ₂ ABT.....	25
11.5	Field recovery test.....	25
11.6	Accuracy test using certified reference material	26
11.6.1	General	26
11.6.2	Gaseous Hg ⁰ sorbent trap spiking system.....	26
12	Calculations, data reduction, data analysis and reporting	26
12.1	Calculation of pre-sampling spiking level	26
12.2	Calculations of the flow reference ratio for flow-proportional sampling.....	27
12.3	Calculation of spike recovery	27
12.4	Calculation of breakthrough.....	28
12.5	Calculation of mercury concentration	28
12.6	Calculation of paired trap agreement	29
12.7	Calculation of FRT parameters	29
12.8	Data reduction and method uncertainty.....	30
Annex A (informative)	Gaseous Hg ⁰ sorbent trap spiking system	31
Annex B (informative)	Calculation of flue gas moisture content	35
B.1	Plants with wet abatement systems.....	35
B.2	Plants without wet abatement systems.....	35
B.2.1	General	35
B.2.2	Calculating moisture content from a stoichiometric fuel factor.....	35
B.2.3	Calculating moisture content from flue gas properties.....	36
Annex C (normative)	Performance criteria and test procedures for certification of long-term sampling systems.....	38
C.1	General requirements.....	38
C.2	Validation of the installation/functioning on each plant.....	39
C.2.1	Preparation.....	39
C.2.1.1	General	39
C.2.1.2	Minimum requirements for set-up.....	39

C.2.1.3	Minimum requirements for selecting the sampling point	39
C.3	Performance criteria and test procedure for certification	39
C.3.1	General relation to other standards.....	39
C.3.2	General requirements	39
C.3.2.1	Application of the minimum requirements.....	39
C.3.2.2	Certification ranges	39
C.3.3	Performance criteria common to all long-term sampling systems for laboratory testing.....	40
C.3.3.1	Performance criteria for the automatic volume proportional flow control.....	40
C.3.3.2	Requirements of EN 15267-3	40
C.3.4	Performance criteria common to all long-term sampling systems for field testing.....	40
C.3.4.1	For the automatic volume proportional flow control.....	40
C.3.4.2	Status information	40
C.3.4.3	Availability	40
C.3.4.4	Reproducibility	41
C.3.4.5	Automatic post-adjustment unit.....	42
C.3.4.6	Breakthrough criteria of used traps	42
C.3.4.7	Paired trap agreement.....	42
C.3.4.8	Number of values to be determined	42
C.3.4.9	Labelling.....	42
C.3.4.10	Relation to the plant conditions	42
C.3.4.11	Volume proportional control	42
C.3.4.12	Essential characteristic data	42
Annex D (informative)	Sorbent traps configurations	43
D.1	Sorbent trap dimensions	43
D.2	Sorbent trap configurations	43
Annex E (normative)	Reporting of sampling information.....	45
E.1	Reporting	45
E.1.1	Short-term sampling	45
E.1.1.1	General	45
E.1.1.2	Basic information.....	45
E.1.1.3	Sampling data for each trap	45
E.1.2	Long-term sampling	46
E.1.3	Interruption of data recording.....	46
E.1.4	Reporting the validation of a long-term sampling system (from the manufacturer and the test laboratory).....	47

Annex F (informative) Example uncertainty budget for mercury measurement using sorbent traps.....	48
F.1 Introduction.....	48
F.2 Elements required for the uncertainty determinations.....	48
F.2.1 Model equation.....	48
F.3 Example of an uncertainty calculation.....	48
F.3.1 Specific conditions in the field.....	48
F.3.2 Performance characteristics	50
F.4 Model equation and application of rule of uncertainty propagation	51
F.4.1 Concentration of Hg	51
F.4.1.1 General	51
F.4.1.2 Calculation of the combined uncertainty of V_m and C_m.....	52
F.4.1.3 Based on Formula (F.1) the combined uncertainty of C_m can be expressed by Formula (F.6):	52
F.4.1.4 Calculation of sensitivity coefficients.....	53
F.4.1.5 Results of the standard uncertainties calculations	53
F.4.1.6 Estimation of the combined uncertainty.....	55
Annex G (informative) Calculation of the uncertainty associated with correcting to dry gas conditions at an oxygen reference concentration	58
G.1 Uncertainty associated with a concentration expressed on dry gas.....	58
G.2 Uncertainty associated with a concentration expressed at an oxygen reference concentration	60
Bibliography	62

European foreword

This document (CEN/TS 17286:2019) has been prepared by Technical Committee CEN/TC 264 “Air quality”, the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

The purpose of this document is to establish performance benchmarks for, and to evaluate the acceptability of, sorbent trap monitoring systems used to monitor total vapour- phase mercury (Hg) emissions in stationary source flue gas streams. These monitoring systems involve continuous repetitive in-flue sampling using paired sorbent traps with subsequent analysis of the time-integrated samples.

This document is suitable for both short-term (periodic) measurements and long-term (continuous) monitoring using sorbent traps.

NOTE When this Technical Specification has been validated, the sorbent trap method will be an Alternative Method subject to the restrictions on applicability defined below. Until that time, EN 13211 is the only accepted Reference Method for both short-term (periodic) measurements and for calibrating continuous monitoring systems, including those with long-term sampling systems. EN 13211 is a wet chemistry approach that relies on absorption of mercury into impinger solutions.

The substance measured according to this specification is the total vapour phase mercury in the flue gas, which represents the sum of the elemental mercury (Hg^0) and gaseous forms of oxidized mercury (Hg^{2+}), such as mercury (II) chloride, in mass concentration units of micrograms (μg) per dry meter cubed (m^3). The analytical range is typically 0,1 to greater than 50 $\mu\text{g}/\text{m}^3$.

The sorbent tube approach is intended for use under relatively low particulate conditions (typically less than 100 mg/m^3) when monitoring downstream of all pollution control devices, e.g. at coal fired power plants and cement plants. In this case, the contribution of mercury in the particulate fraction is considered to be negligible (typically less than 5 % of total mercury). However, it shall be noted that the sorbent trap does take account of the finest particle fraction that is sampled with the flue gas, in addition to capturing the vapour phase mercury.

This specification also contains routine procedures and specifications that are designed to evaluate the ongoing performance of an installed sorbent trap monitoring system. The operator of the industrial installation is responsible for the correct calibration, maintenance and operation of this long-term sampling system. Additional requirements for calibration and quality assurance of the long-term sampling system are then defined in EN 14884 and EN 14181.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 14181, *Stationary source emissions — Quality assurance of automated measuring systems*

EN 14790 (series), *Stationary source emissions — Determination of the water vapour in ducts — Standard reference method*

EN 15259:2007, *Air quality — Measurement of stationary source emissions — Requirements for measurement sections and sites and for the measurement objective, plan and report*

EN 15267 (series), *Air quality — Certification of automated measuring systems*

EN 15853, *Ambient air quality — Standard method for the determination of mercury deposition*

EN ISO 16911-1:2013, *Stationary source emissions — Manual and automatic determination of velocity and volume flow rate in ducts — Part 1: Manual reference method (ISO 16911-1:2013)*