PD ISO/TR 13086-4:2019

BSI Standards Publication

Gas cylinders — Guidance for design of composite cylinders

Part 4: Cyclic fatigue of fibres and liners

bsi.

National foreword

This Published Document is the UK implementation of ISO/TR 13086-4:2019.

The UK participation in its preparation was entrusted to Technical Committee PVE/3/3, Transportable Gas Containers - Cylinder Design, Construction and Testing at the Time of Manufacture.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Published by BSI Standards Limited 2019

ISBN 978 0 580 98768 7

ICS 23.020.35

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2019.

Amendments/corrigenda issued since publication

Date	Text affected

PD ISO/TR 13086-4:2019

TECHNICAL REPORT

ISO/TR 13086-4

First edition
2019-09

Gas cylinders — Guidance for design of composite cylinders —

Part 4: Cyclic fatigue of fibres and liners

Reference number
ISO/TR 13086-4:2019(E)

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 3, *Cylinder design*.

A list of all parts in the ISO 13086 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

TECHNICAL REPORT **ISO/TR 13086-4:2019(E)**

Gas cylinders — Guidance for design of composite cylinders —

Part 4: Cyclic fatigue of fibres and liners

1 Scope

This document addresses the topic of cyclic fatigue of structural reinforcing fibres as used in composite cylinders, and cyclic fatigue of structural and non-structural liners in these cylinders. This document provides a basic level of understanding of these topics.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

NOTE Terms and definitions related to gas cylinders can be found in ISO 10286.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at http://www.electropedia.org/

— ISO Online browsing platform: available at https://www.iso.org/obp

4 Background

Composite cylinders began service in the 1950s, initially as rocket motor cases with glass fibre reinforcement. This soon led to glass fibre pressure vessels with rubber liners, and then to glass fibre pressure vessels with metal liners. Metal liners were typically either aluminium alloy or steel. Eventually, new structural fibres, such as aramid and carbon, came into use for reinforcing pressure vessels. Today, typical reinforcements for composite gas cylinders are glass and carbon, either individually or together as a hybrid. Typical liner materials are steel, aluminium alloy or polymers, for example, high-density polyethylene (HDPE) or polyamide (PA); other materials may be acceptable.

Each of these materials is subject to cyclic fatigue based on the type of service and the construction of the cylinder. Cylinders used in transport service generally see full range cycles, with a limited number of cycles per year. Cylinders used as fuel containers would typically see up to three pressure cycles per day for fleet vehicles, and less for private vehicles. Cylinders used in stationary applications such as refuelling cascades could see a very large number of partial cycles in a year. Some cylinders could see a combination of these conditions. Stationary cylinders used for fuel cells or emergency breathing applications could see a very limited number of cycles. Design working pressures for high pressure cylinders are typically in the range of 20 bar to 1 100 bar. Cylinders for liquified gases such as propane may operate at pressures up to 20 bar, and normally see fewer pressure cycles.

The different reinforcing fibres have different fatigue lives for a given stress or strain range. Liner materials will also have different fatigue lives for a given stress or strain range. The load-sharing characteristics of a liner material with a given reinforcement will affect their fatigue lives. An autofrettage cycle is used with metal lined cylinders to improve fatigue life. The low modulus of

