

BSI Standards Publication

Image quality evaluation methods for printed matter

Part 11: Colour gamut analysis



National foreword

This Published Document is the UK implementation of ISO/TS 18621-11:2019.

The UK participation in its preparation was entrusted to Technical Committee PAI/43, Graphic technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020 Published by BSI Standards Limited 2020

ISBN 978 0 539 01278 1

ICS 37.100.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 January 2020.

Amendments/corrigenda issued since publication

Date Text affected

PD ISO/TS 18621-11:2019

TECHNICAL SPECIFICATION

ISO/TS 18621-11

First edition 2019-12

Image quality evaluation methods for printed matter —

Part 11:

Colour gamut analysis



PD ISO/TS 18621-11:2019 **ISO/TS 18621-11:2019(E)**



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents				Page	
Fore	word			iv	
Introduction				v	
1					
	-	Scope			
2	Normative references			1	
3	Tern	Terms and definitions			
4	Describing a colour gamut				
	4.1 General				
	4.2		ements of a gamut boundary description		
	4.3	Device	gamut and usable gamut	3	
	4.4	Proced	ures for describing a colour gamut	3	
		4.4.1		3	
		4.4.2	Procedure for describing the colour gamut of a reproduction system based on its ICC profile	3	
		4.4.3	Procedure for describing the device gamut of a reproduction system based on its characterization model	5	
		4.4.4	Procedure for describing the device gamut of a reproduction system based on measurement of a printed gamut target	5	
		4.4.5	Procedure for describing the device gamut of a reproduction system based on characterization data		
5	Computing the volume of a colour reproduction gamut			5	
	5.1	Genera	1	5	
	5.2	Volume	e of a single gamut	5	
		5.2.1	Volume calculation	5	
		5.2.2	Verifying the volume calculation	6	
	5.3		e of the intersection of two gamuts	7	
		5.3.1			
		5.3.2	Determining if a coordinate is inside or outside a gamut	7	
6	Comparing colour gamuts			8	
	6.1	Genera	1	8	
	6.3		coverage		
	6.4	Out-of-	gamut	8	
7	Enco	oding and communicating a colour gamut description			
Anne	ex A (in CMY	formative K printin	e) Images for use in determining the gamut boundary of RGB and ag processes	10	
Anne		-	e) Gamut volumes for a set of reference profiles		
Annex C (informative) Errors in triangulation					
Annex D (normative) Media-relative colour gamuts				14	
Rihli	ograph	ıv		15	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 130, Graphic technology.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The colour gamut that can be achieved by a reproduction system is an important attribute. It enables users to compare the colour reproduction capabilities of different printing systems and to determine whether one system can simulate all the colours available in another. This document describes procedures to define and compare colour gamuts.

Given a set of coordinates known to lie on the surface of a colour gamut, the volume of the gamut can be determined by segmenting the gamut into a series of tetrahedra, computing the volume of each tetrahedron and summing the results. For a reproduction process with three colour components, a colour will lie on the surface if it satisfies the condition that at least one component has a value of 0 or 1, where 1 represents the maximum amount of the colour component. However, printing processes usually have four or more colour components (e.g. Cyan, Magenta, Yellow and Black in four-colour process printing), and determining which coordinates lie on the gamut boundary cannot be done solely from the relative amounts of the colour components. For CMYK processes, in almost all cases, the Black colorant extends the gamut below the gamut vertex at each hue angle. This makes it possible to identify a set of coordinates which are expected to lie on the gamut surface from the relative colorant amounts. For processes with more than four colour components, some knowledge of the colorimetry of a sample of colours from the colour data encoding is needed in order to determine which colours lie on the boundary.

For these reasons, coordinates on the surface of the gamut of RGB and CMYK printing processes can be determined by printing a test chart with suitable colorant combinations, and measuring the colours; while for other printing processes, it is necessary to model the colorant-to-colorimetry relationship in order to identify colours on the gamut boundary.

Image quality evaluation methods for printed matter —

Part 11:

Colour gamut analysis

1 Scope

This document defines procedures to measure and compare the colour gamuts of RGB and CMYK printing processes.

It is not applicable to other printing processes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15076-1, Image technology colour management — Architecture, profile format and data structure — Part 1: Based on ICC.1:2010

ISO 12642-1, Graphic technology — Input data for characterization of four-colour process printing — Part 1: Initial data set

ISO 13655, Graphic technology — Spectral measurement and colorimetric computation for graphic arts images

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

colour gamut

range of colours that can be reproduced by an output device on a given medium, represented in a CIE-based colour space

Note 1 to entry: The CIE colour space for representation of colour gamuts is normally CIELAB.

3.2

gamut vertex

coordinate in a CIE-based colour space which represents a point on a colour gamut surface and which is used in defining the surface of the gamut