BS 3L 500:2011+A1:2017



BSI Standards Publication

Procedure for inspection, testing and acceptance of wrought magnesium base alloys



BS 3L 500:2011+A1:2017 BRITISH STANDARD

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2017

Published by BSI Standards Limited 2017

ISBN 978 0 580 97048 1

ICS 49.025.99

The following BSI references relate to the work on this document:

Committee reference ACE/61

Drafts for comment 10/30216237 DC; 17/30354462 DC

Amendments/corrigenda issued since publication

Date Text affected

30 September 2017 A1 – See Foreword

Contents		Page
	Foreword	
	Section 1: General requirements	iv 1
1	Scope	1
2	Normative references	1
3	Definitions	1
4	General	3
5	Information and requirements to be agreed and to be documented	4
6	Manufacture and freedom from defects	6
7	Heat treatment	6
8	Chemical composition	6
9	Testing	7
10	Marking	8
11	Protection and packaging	8
12	Certification	8
	Section 2: Cast billets and slabs for hot working	10
13	General	10
14	Condition	10
15	Dimensions and tolerances	10
16	Internal and external defects	10
17	Retesting procedure	10
18	Marking	10
	Section 3: Extruded bar and section for forging	12
19	General	12
20	Condition	12
21	Dimensions and tolerances	12
22	Selection and preparation of mechanical test samples	12
	Table 1 — Batch sizes for extruded bar and section for forging	12
23	Tensile testing	13
24	Etch inspection	13
25	Fracture test	13
26	Internal defects	14
27	External defects	14
28	Retesting procedures for etch inspection, fracture test and external defects	14
29	Marking	14
	Section 4: Bars for machining and extruded sections	15
30	General	15
31	Condition	15
32	Dimensional tolerances	15
	Table 2 — Tolerances for bars for machining and extruded sections	16
33	Selection and preparation of mechanical test samples	16
	Table 3 — Batch sizes for bars for machining and extruded sections	16
34	Tensile testing	17
35	Etch inspection	17
36	Internal defects	17
37	Retesting procedures for etch inspection, fracture test and external defects	17
38	Marking	17
	Section 5: Forgings	19
39	General	19

40	Manufacture	19
41	Pre-production forgings	19
42	Production forgings	20
43	Procedure X for process control testing	20
	Table 4 — Maximum number of forgings to be manufactured between the collection of test samples	21
45	Batch acceptance tensile tests	21
	Table 5 — Tensile property requirements for forgings	23
46	External defects	23
47	Internal defects	23
48	Grain flow and grain size	23
49	Special tests	24
50	Marking	24
	Section 6: Sheet and strip	25
51	General	25
52	Condition	25
53	Dimensional tolerances	25
	Table 6 — Tolerances for sheet and strip	25
54	Selection and preparation of mechanical test samples	25
55	Tensile testing	26
56	Marking	26
	Section 7: Plate	27
57	General	27
58	Condition	27
59	Dimensional tolerances	27
	Table 7 — Tolerances for plate	27
60	Selection and preparation of mechanical test samples	27
	Table 8 — Direction of tensile test samples and position of tensile test pieces	28
61	Tensile testing	28
62	Internal defects	28
63	Marking	28
<i>C</i> A	Section 8: Tube	29
64	General	29
65	Manufacture Condition	29
66	Dimensional tolerances	29
67		29 29
68	Table 9 — Tolerances for tube Selection and preparation of mechanical test samples	29
00	Table 10 — Batch sizes for tubes	29
69	Tensile testing	30
70	Marking	30
Annex A	(normative) Rules for application of values for chemical composition and mechanical	
	properties given in material specifications	31
Annex B	(normative) Protection against corrosion	31
	Table B.1 — Standard routes for protection against corrosion	34
Annex C	(normative) Tolerances for bars and extruded sections	35
	Table C.1 — Tolerances on straightness of bars and regular sections	37
	Table C.2 — Tolerances on twist of extruded sections	37
	Table C.3 — Tolerances on angles of regular sections	37
	Table C.4 — Tolerances on lengths of bars and extruded sections	37

	Table C.5 — Tolerances on thickness of bars and regular sections	38
	Table C.6 — Tolerances on thickness of hollow sections	38
	Table C.7 — Tolerances on diameters, overall widths and widths across flats of bars, regular	
	sections and hollow sections	39
	Table C.8 — Tolerances on open ends of channels and I beams	40
	Table C.9 — Normal radii for corners on square and rectangular sections (informative)	42
	Table C.10 — Normal radii for corners on rectangular sections: angle, channel, I and T sections	
	(informative)	42
Annex D	(normative) Tolerances for sheet, strip and plate	42
	Table D.1 — Tolerances on thickness of sheet and strip	43
	Table D.2 — Tolerances on thickness of plate	44
	Table D.3 — Cutting tolerances for sheet and plate	44
	Table D.4 — Shearing tolerances for strip	45
	Table D.5 — Tolerances on flatness of plate	45
Annex E	(normative) Tolerances for tube	45
	Table E.1 — Tolerances on straightness of tube	45
	Table E.2 — Tolerances on lengths of tube	46
	Table E.3 — Tolerances on outside and inside diameters of extruded round tube	46
	Table F. 4 — Tolerances on wall thickness of extruded round tube	47

Summary of pages

This document comprises a front cover, and inside front cover, pages i to vi, pages 1 to 47, an inside back cover and a back cover.

BS 3L 500:2011+A1:2017 **BRITISH STANDARD**

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution and came into effect on 31 December 2011. It was prepared by Panel ACE/61/-/24, Light alloys, under the authority of Technical Committee ACE/61, Metallic materials for aerospace purposes. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

BS 3L 500:2011 superseded BS 2L 500:1973, which has been withdrawn.

BS 3L 500:2011+A1:2017 supersedes BS 3L 500:2011, which is withdrawn.

Information about this document

BS 3L 500:2011 was a full revision of the standard, and introduced the following principal changes.

Section 1:

- a) Information to be supplied by purchaser added.
- b) Information to be agreed by manufacturer and purchaser added.
- c) Heat treatment requirements added.
- d) Application of values requirements added.
- e) Tensile testing at ambient temperature to BS A4-1.1 replaced by BS EN 2002-1.

Section 5:

External and internal defects requirements added.

Section 6:

Position of tensile test piece requirements added.

Section 7:

Position of tensile test piece requirements added.

Appendix A: Re-identified as Annex A (Rules for application of values for chemical composition and mechanical properties given in material specifications).

Appendix B: Re-identified as Annex B (Protection against corrosion).

Appendix C: Re-identified as Annex C (Tolerances for bars and extruded sections).

Appendix D: Re-identified as Annex D (Tolerances for sheet, strip and plate).

Appendix E: Re-identified as Annex E (Tolerances for tube).

Text introduced or altered by Amendment No. 1 is indicated in the text by tags [A]. Minor editorial changes are not tagged.

Hazard warnings

WARNING. This British Standard calls for the use of substances and/or procedures that can be injurious to health if adequate precautions are not taken. It refers only to technical suitability and does not absolve the user from legal obligations relating to health and safety at any stage.

BRITISH STANDARD BS 3L 500:2011+A1:2017

Use of this document

It has been assumed in the preparation of this British Standard that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

BS 3L 500:2011+A1:2017 BRITISH STANDARD

BRITISH STANDARD BS 3L 500:2011+A1:2017

Section 1: General requirements

1 Scope

This British Standard specifies procedures for inspection, testing and acceptance of wrought magnesium-base alloys for aerospace purposes.

The standard is applicable to material specifications in the British Standard Aerospace L series and also to other British Standard material specifications for wrought magnesium-base alloys which are suitable for aerospace use.

Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS M 93, Protection of magnesium — Rich alloys against corrosion — Specification

BS X 38, Heat curing paint scheme for aerospace purposes — Specification

BS EN 2002-1, Metallic materials — Test methods — Part 1: Tensile testing at ambient temperature

EN 2002-16, Metallic materials — Test methods — Part 16: Non-destructive testing — Penetrant testing¹

EN 4050-2, Aerospace series — Test method for metallic materials — Ultrasonic inspection of bars, plates, forging stock and forgings — Part 2: Performance of test¹

EN 4050-4, Aerospace series — Test method for metallic materials — Ultrasonic inspection of bars, plates, forging stock and forgings — Part 4: Acceptance criteria¹

Definitions 3

For the purposes of this British Standard, the following terms and definitions apply.

3.1 approved scrap

scrap which has been segregated and identified as being derived from material, the composition of which has been established with regard to the complete range of both alloying and impurity elements given in the material specification

3.2 bar

wrought material of uniformly round, half round, square, rectangular, hexagonal, octagonal or regular polygonal solid section supplied in straight lengths

3.3 batch

material which is of the same product form and of the same nominal dimensions; from the same cast; manufactured in the same production period; from the same heat treatment charge

NOTE 1 In the case of solution heat treatment in a continuous furnace, material from a maximum period of 8 h is regarded as the same heat treatment charge.

NOTE 2 Where applicable, batch sizes for specific products are given in the relevant sections of this standard.

Published as ASD Prestandard at the date of publication of this standard.