

BS 5489-2:2016



BSI Standards Publication

1915070_pre.pdf

Code of practice for the design of road lighting — Part 2: Lighting of tunnels

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2016

Published by BSI Standards Limited 2016

ISBN 978 0 580 85616 7

ICS 93.080.40

The following BSI references relate to the work on this document:

Committee reference EL/1/3

Draft for comment 15/30296173 DC

Publication history

First published September 1974

Second edition March 1987

Third edition August 1992

Fourth edition December 2003

Fifth (present) edition April 2016

Amendments issued since publication

Date	Text affected
------	---------------

Contents

Foreword *ii*

1	Scope	1
2	Normative references	1
3	Terms, definitions and symbols	1
4	Tunnel conditions	5
5	Tunnel lighting design	6
6	Calculation and measurement	13

Annexes

Annex A (informative)	Tunnel design, use and operational aspects that affect tunnel lighting design	17
Annex B (informative)	Lighting systems	18
Annex C (normative)	Daytime lighting of short tunnels	19
Annex D (informative)	Types of daytime lighting for short tunnels	23
Annex E (normative)	Determination of access zone luminance by direct measurement	24
Annex F (normative)	Determination of access zone luminance by the grid method	25
Annex G (normative)	Estimation of the access zone luminance	30
Annex H (informative)	Uncertainty in measurement of illuminance	31

Bibliography 35

List of figures

Figure 1	Tunnel lighting class selection	7
Figure 2	Luminance reduction curve	9
Figure 3	Interior zone measurement positions	16
Figure B.1	Symmetrical lighting system	19
Figure B.2	Counterbeam lighting system	19
Figure C.1	Look-through percentage	20
Figure C.2	Visual angles	21
Figure C.3	Visibility of a car	22
Figure C.4	Visibility of a pedestrian/cyclist	23
Figure F.1	Perspective view of a tunnel entrance with superimposed 20° subtense circle	26
Figure F.2	20° field of view divided into assessment areas	27
Figure G.1	Examples of tunnel approaches giving access zone luminances to be used	30

List of tables

Table 1	Stopping sight distances for various design speeds	6
Table 2	Traffic flow	7
Table 3	Values of k for different speed limits and tunnel lighting classes	8
Table 4	Road surface luminance of the interior zone	9
Table 5	Uniformity of the road surface luminance	10
Table C.1	Transverse position of object and observer	22
Table F.1	Typical luminance values	28
Table F.2	Example of determination of access zone luminance	29
Table H.1	Typical uncertainties in parameters and examples of their effect on illuminance values	33

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 36, an inside back cover and a back cover.

Foreword

Publishing information

This part of BS 5489 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 30 April 2016. It was prepared by Subcommittee EL/1/3, *Tunnel lighting*, under the authority of Technical Committee EL/1, *Light and lighting*. A list of organizations represented on these committees can be obtained on request to their secretary.

Supersession

This part of BS 5489 supersedes BS 5489-2:2003+A1:2008, which is withdrawn.

Relationship with other publications

BS 5489 consists of two parts:

- Part 1: *Lighting of roads and public amenity areas*;
- Part 2: *Lighting of tunnels*.

Information about this document

This is a full revision of the standard to align the standard with current best practice.

The aim of this standard is to promote wider understanding of the lighting of tunnels for motorized and mixed traffic and to give guidance on the design decisions that need to be made. It contains recommendations that are essential to the design process and that will enable production of designs that are appropriate and justifiable.

Use of this document

As a code of practice, this part of BS 5489 takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this part of BS 5489 is expected to be able to justify any course of action that deviates from its recommendations.

It has been assumed in the preparation of this part of BS 5489 that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

The design of lighting for tunnels is a complex process with many different aspects and therefore it is important that this standard is read thoroughly to ensure that all relevant issues are taken into account.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

The word "should" is used to express recommendations of this standard. The word "may" is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the clause. The word "can" is used to express possibility, e.g. a consequence of an action or an event.

Notes and commentaries are provided throughout the text of this standard. Notes give references and additional information that are important but do not form part of the recommendations. Commentaries give background information.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

1 Scope

This part of BS 5489 gives recommendations for the design of the lighting of tunnels for motorized and mixed traffic. It is applicable to all types of road, including motorways.

This standard is applicable to those aspects of lighting that are concerned with traffic safety, such as arrangements, levels and other parameters including daylight.

This standard is not applicable to aspects of lighting that concern aesthetics.

This part of BS 5489 is not applicable to the lighting of underpasses or subways reserved for pedestrians or cyclists, which is covered in BS 5489-1.

NOTE 1 This part of BS 5489 is based on photometric considerations, and all values of luminance and illuminance are maintained levels.

NOTE 2 In this standard "lamp" and "lamps" also include LED light sources.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 667, *Illuminance meters – Requirements and test methods*

BS 7920, *Luminance meters – Requirements and test methods*

BS EN 12665, *Light and lighting – Basic terms and criteria for specifying lighting requirements*

BS EN 13201-2, *Road lighting – Part 2: Performance requirements*

BS EN 13201-3:2015, *Road lighting – Part 3: Calculation of performance*

BS EN 13201-4, *Road lighting – Part 4: Methods of measuring lighting performance*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this part of BS 5489, the terms and definitions given in BS EN 12665, BS EN 13201-2, BS EN 13201-3 and the following apply.

3.1.1 access zone

part of the open road immediately in front of an entrance portal, covering the distance over which an approaching driver can see into a tunnel

3.1.2 access zone length

distance between the stopping sight distance point ahead of an entrance portal and the entrance portal itself

3.1.3 access zone luminance

average luminance contained in a conical field of view, subtending an angle of 20° with the apex at the position of the eye of an approaching driver and aimed at the centre of the entrance portal

NOTE Access zone luminance is assessed from a point at a distance equal to the stopping sight distance from the entrance portal and 1.5 m above the middle of the relevant carriageway or traffic lane.