



BSI Standards Publication

Power cables with XLPE insulation and metal sheath, and their accessories, for rated voltages from 66 kV ($U_m = 72.5$ kV) to 132 kV ($U_m = 145$ kV)

(Implementation of HD 632)

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2017

Published by BSI Standards Limited 2017

ISBN 978 0 580 96958 4

ICS 29.060.20

The following BSI references relate to the work on this document:

Committee reference GEL/20/16

Drafts for comment 12/30244367 DC; 17/30354015 DC

Amendments/corrigenda issued since publication

Date	Text affected
February 2015	C1.
January 2016	C2.
July 2017	A1. See Foreword for details.

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Voltage designation and cable design features	3
4.1 Voltage designation	3
<i>Table 1 — Test voltages</i>	4
4.2 Cable maximum temperatures	5
<i>Table 2 — Cable maximum temperatures</i>	5
4.3 Semi-conducting screens	5
4.4 Metal cable sheathing materials and metal screen	5
4.5 Oversheath materials	5
4.6 Precautions against water penetration in cables	5
5 Marking of cables	6
5.1 External marking	6
5.2 Identification of year and month of manufacture	6
5.3 Mark of an approval organization	6
6 Cable characteristics	6
7 Accessory characteristics	7
8 Test conditions	7
8.1 Ambient temperature	7
8.2 Frequency and waveform of power frequency test voltage	8
8.3 Waveform of impulse test voltage	8
9 Routine tests on cables and on the main insulation of prefabricated accessories	8
9.1 General	8
9.2 Partial discharge test	8
9.3 Voltage test	9
9.4 Electrical test on oversheath of the cable	9
10 Sample tests	9
10.1 Cables	9
<i>Table 3 — Number of samples for sample tests</i>	9
<i>Table 4 — Test conditions and requirements for particular characteristics of cable insulating materials</i>	10
10.2 Accessories	16
11 Type tests — Summary	16
11.1 General	16
11.2 Range of type approval for cables	17
11.3 Range of type approval for accessories	17
11.4 Summary of type approval tests	18
<i>Table 5 — Type tests on cable components</i>	18
12 Electrical type tests on cables	19
12.1 Electrical tests on complete cable	19
12.2 Sequence of tests	19
12.3 Special provisions	19
12.4 Check on insulation thickness of cable for electrical type tests	20
12.5 Bending test	20
12.6 Partial discharge test	20
12.7 Tan δ measurement as a function of the voltage and capacitance measurement	21

<i>Table 6 — Tan δ in relation to voltage</i>	21
12.8 Tan δ measurement at high temperature	21
12.9 Heating cycle voltage test	21
12.10 Impulse voltage test	22
12.11 Power frequency voltage test	22
<i>Table 7 — Power frequency voltage test</i>	22
12.12 Cable examination	22
13 Type tests on cable components	23
13.1 Check of cable construction	23
13.2 Ageing tests on pieces of complete cable to check compatibility of materials	23
<i>Table 8 — Tests and requirements for mechanical characteristics of XLPE insulating material before and after ageing</i>	24
<i>Table 9 — Test requirements for particular characteristics of oversheathing for cables</i>	24
13.3 Tests for determining the mechanical properties of insulation and oversheathing before and after ageing	25
13.4 Pressure test at high temperature on oversheaths	25
13.5 Test on PVC oversheaths (ST ₁ and ST ₂) at low temperature	25
13.6 Loss of mass test on PVC oversheaths of type ST ₂	26
13.7 Heat shock test for PVC oversheaths (ST ₁ and ST ₂)	26
13.8 Visual examination of semi-conducting screens	26
13.9 Hot set test for XLPE insulation	26
13.10 Measurement of carbon black content of black PE oversheaths (ST ₃ and ST ₇)	27
13.11 Shrinkage test for cable insulation	27
<i>Figure 1 — Shrinkage test</i>	27
13.12 Shrinkage test on polyethylene sheath	27
13.13 Test under fire conditions	27
14 Longitudinal water penetration type test on complete cables	27
14.1 Sampling	27
<i>Figure 2 — Schematic diagram of apparatus of water penetration test</i>	28
14.2 Procedure	28
14.3 Requirement	29
14.4 Additional procedure for phase conductor	29
15 Mechanical and thermal type tests on complete cables	29
15.1 General	29
15.2 Impact test	29
15.3 Abrasion, penetration, bending and saline bath tests on anti-corrosion coverings for self-contained cables	29
<i>Figure 3 — Toothed wheel: 15 teeth</i>	31
<i>Figure 4 — Possible arrangement of sample in saline bath</i>	32
15.4 Corrosion penetration test for aluminium sheathed cables	32
15.5 Internal thermal resistance of complete cable	33
16 Type tests on accessories	34
16.1 General	34
16.2 Tests and requirements	34
16.3 Partial discharge test	35
16.4 Load cycle voltage test	35
16.5 Impulse voltage test	35
16.6 Power frequency voltage test	35
16.7 Examination	35
16.8 Tests on buried joints	35

	<i>Table 10 — Lightning impulse voltage test levels</i>	36
16.9	Test for accessories with mechanical connections to sheath or screen wires	37
16.10	SF ₆ switchgear cable connections	38
17	Type tests on ancillary equipment	38
18	Electrical tests after installation	38
18.1	Testing of insulation (cable and accessory)	38
	<i>Table 11 — A.C. test voltages</i>	38
18.2	Verification of specially bonded sheath systems	38
	<i>Table 12 — Maximum contact resistance values</i>	39
18.3	Verification of positive phase and zero sequence impedance	39
18.4	D.C. conductor resistance test	41
18.5	Voltage test on sheath insulation	41
18.6	Test on sheath voltage limiters	41
	<i>Table 13 — Voltage and current range for maintenance test on silicon carbide units</i>	42
Annex A	(normative) Tests and requirements for cable bonding leads	43
	<i>Table A.1 — Examples of the construction of single core bonding leads</i>	44
	<i>Table A.2 — Examples of the construction of concentric bonding leads</i>	45
	<i>Table A.3 — Test voltages for bonding leads</i>	47
	<i>Table A.4 — Conductor d.c. resistance</i>	47
Annex B	(normative) Tests and requirements for sheath voltage limiters (SVLs)	48
Annex C	(normative) Tests and requirements for link housings	50
Annex D	(normative) Additional water blocking test for phase conductor	53
	<i>Figure D.1 — Apparatus for water penetration test</i>	54
	Bibliography	55

Summary of pages

This document comprises a front cover, and inside front cover, pages i to vi, pages 1 to 55, an inside back cover and a back cover.

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 December 2012. It was prepared by Subcommittee GEL/20/16, *Medium/high voltage cables*, under the authority of Technical Committee GEL/20, *Electric cables*. A list of organizations represented on these committees can be obtained on request to their secretary.

Supersession

BS 7912:2012 superseded BS 7912:2001, which has been withdrawn.

BS 7912:2012+A1:2017 supersedes BS 7912:2012, which is withdrawn.

Relationship with other publications

BS 7912:2012 implemented the nationally applicable parts of Harmonization Document HD 632 S2:2008 published by the European Committee for Electrotechnical Standardization (CENELEC), in accordance with the decision of the CENELEC Technical Board.

Information about this document

BS 7912:2012 was a full revision of the standard, and introduced the following principal changes:

- alignment with the latest version of HD 632 S2:2008, part 1, being itself identical to Edition 4 of IEC 60840;
- inclusion of matter relating to BS 7970, which was also revised in parallel.

Text introduced or altered by Amendment No. 1 is indicated in the text by tags **A1** **A1**. Minor editorial corrections are not tagged. Amendment A1 introduces the following principal changes:

- replacement of subclause **4.6** with new text;
- replacement of Clause **9** with new text;
- expansion/restructure of Clause **10** to include accessories;
- replacement of subclause **10.1.7** (previously **10.7**) with new text;
- addition of new subclause **10.2**;
- alteration to subclause **14.1**;
- replacement of **subclause D.1** with new text;
- replacement of **Figure D.1** with new figure.

Product certification/inspection/testing

Users of this British Standard are advised to consider the desirability of third-party certification/inspection/testing of product conformity with this British Standard. Users seeking assistance in identifying appropriate conformity assessment bodies or schemes may ask BSI to forward their enquiries to the relevant association.

Hazard warnings

<p>WARNING. This British Standard calls for the use of substances and/or procedures that can be injurious to health if adequate precautions are not taken. It refers only to technical suitability and does not absolve the user from legal obligations relating to health and safety at any stage.</p>
--

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is “shall”.

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

1 Scope

This British Standard specifies tests and requirements for power cables with XLPE insulation and metal sheath and their accessories for rated voltages from 66 kV ($U_m = 72.5$ kV) to 132 kV ($U_m = 145$ kV) for fixed installations.

NOTE 1 Cable systems to this standard do not normally have high electrical stresses at the conductor or insulation screen. If the calculated nominal electrical stresses at the conductor screen will be higher than 8.0 kV/mm and/or at the insulation screen higher than 4.0 kV/mm, then attention is drawn to the need to conduct a prequalification test in accordance with IEC 60840:2011, Clause 13.

This British Standard is applicable to single-core cables and three-core cables with separate cores and to their accessories for usual conditions of installation and operation. It is not applicable to special cables and their accessories, such as those designed for submarine cables, for which modification to the standard tests might be necessary or special test conditions might need to be devised.

NOTE 2 Annex A gives tests and requirements for cable bonding leads. Annex B gives tests and requirements for sheath voltage limiters (SVLs), while Annex C gives tests and requirements for link housings. Annex D gives an additional water blocking test for phase conductors.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 7870-2:2011, *LV and MV polymeric insulated cables for use by distribution and generation utilities — Part 2: Methods of test*

BS 7970, *Electric cables — Metal foil and longitudinally welded aluminium sheath constructions of power cables having XLPE insulation for rated voltages from 66 kV ($U_m = 72.5$ kV) to 132 kV ($U_m = 145$ kV)*

BS EN 60060-1, *High-voltage test techniques — Part 1: General definitions and test requirements*

BS EN 60228, *Conductors of insulated cables*

BS EN 60229:2008, *Electric cables — Tests on extruded oversheaths with a special protective function*

BS EN 60230, *Impulse tests on cables and their accessories*

BS EN 60287-1-1, *Electric cables — Calculation of the current rating — Part 1-1: Current rating equations (100% load factor) and calculation of losses — General*

BS EN 60332-1-2:2004, *Tests on electric and optical fibre cables under fire conditions — Part 1-2: Test for vertical flame propagation for a single insulated wire or cable — Procedure for 1 kW pre-mixed flame*

BS EN 60811-201, *Electric and optical fibre cables — Test methods for non-metallic materials — Part 201: General test — Measurement of insulation thickness*

BS EN 60811-202, *Electric and optical fibre cables — Test methods for non-metallic materials — Part 202: General test — Measurement of thickness of non-metallic sheath*

BS EN 60811-401, *Electric and optical fibre cables — Test methods for non-metallic materials — Part 401: Miscellaneous tests — Thermal ageing methods — Ageing in an air oven*

BS EN 60811-409, *Electric and optical fibre cables — Test methods for non-metallic materials — Part 409: Miscellaneous tests — Loss of mass test for thermoplastic insulations and sheaths*