



BSI Standards Publication

Public transport — Service interface for real-time information relating to public transport operations

Part 5: Functional service interfaces
situation exchange: Situation Exchange

National foreword

This Published Document is the UK implementation of CEN/TS 15531-5:2016. It supersedes DD CEN/TS 15531-5:2011 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EPL/278, Intelligent transport systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.

Published by BSI Standards Limited 2016

ISBN 978 0 580 91099 9

ICS 35.240.60

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2016.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CEN/TS 15531-5

May 2016

ICS 35.240.60

Supersedes CEN/TS 15531-5:2011

English Version

**Public transport - Service interface for real-time
information relating to public transport operations - Part
5: Functional service interfaces situation exchange:
Situation Exchange**

Transport public - Interface de service pour les
informations en temps réel relatives aux opérations de
transport public - Partie 5: Service d'interface
fonctionnelle - Échange de l'état de l'exploitation et de
son contexte

Öffentlicher Verkehr - Diensteschnittstelle für den
Echtzeitaustausch von Betriebsinformationen des
ÖPNV (SIRI) - Teil 5: Funktionelle Serviceschnittstelle:
Situativer Austausch

This Technical Specification (CEN/TS) was approved by CEN on 25 February 2016 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

European foreword.....	6
Introduction	8
1 Scope	10
2 Normative references	11
3 Terms and definitions	11
4 Symbols and abbreviations	16
5 Situations as Software Entities.....	16
5.1 General.....	16
5.2 Structured Situations.....	17
5.3 Distributed Situation processing.....	18
5.3.1 Identity and Write-Only Updates.....	18
5.3.2 Currency and the Situation Life Cycle	19
5.3.3 Representational model for Situation Elements.....	20
5.3.4 Update chains – Causal chains.....	21
5.3.5 Cross-referencing Situations – Causal chains	22
5.3.6 Branching and distributed updates.....	22
5.3.7 Archiving.....	24
5.4 Summary of Situation Management	24
5.4.1 General.....	24
5.4.2 Situation Identity.....	24
5.4.3 Situation Life Cycle	25
5.4.4 Situation Update Content	25
5.4.5 Example of identifier allocation.....	26
5.4.6 Date time stamps as identifiers.....	26
5.5 Interoperability of Situation management systems.....	26
5.5.1 General.....	26
5.5.2 Datex2 Interoperability	27
5.5.3 TPEG Interoperability	28
5.5.4 Communications Bandwidth.....	28
6 The Situation Model	28
6.1 General.....	28
6.2 Representing a PT Situation in SIRI-SX	29
6.2.1 Summary of PT Situation model	29
6.2.2 PT Situation Element Body	30
6.2.3 PT Situation Body Details.....	31
6.2.4 PT Situation Reason	33
6.2.5 Situation Consequence	36
6.2.6 The PT AffectsScope	37
6.3 Representing a Road Situation in SIRI-SX	43
6.3.1 Summary of Road Situation model	43
6.3.2 Road Situation Element Body	45
6.3.3 Common Accessibility.....	45
6.3.4 Publishing Actions	46
6.3.5 Common Types.....	47

7	Situation Exchange Service [SX]	54
7.1	Purpose	54
7.2	Description	54
7.3	Reference Data	54
7.4	Capability and Permission Matrices	54
7.4.1	Capability Matrix	54
7.4.2	Permission Matrix	56
7.5	UML Diagrammatic Representation	56
7.5.1	General	56
7.5.2	UML Detailed Diagram of SituationExchangeRequest	57
7.5.3	UML Diagram of SituationExchangeDelivery - Summary	59
7.5.4	UML Diagram of SituationExchangeDelivery - Detail	60
7.5.5	UML Diagram of SituationContext	60
7.6	SituationExchangeRequest	61
7.6.1	SituationExchangeRequest Definition	61
7.6.2	SituationStatusFilter Definition	63
7.6.3	SituationNetworkFilter Definition	64
7.6.4	SituationStopPlaceFilter Definition	64
7.6.5	SituationJourneyFilter Definition	65
7.6.6	SituationPlaceFilter Definition	65
7.6.7	SituationRoadFilter Definition	65
7.6.8	AccessibilityNeedFilter Definition	66
7.6.9	SituationExchangeRequest Example	66
7.7	SituationExchangeSubscriptionRequest	66
7.7.1	SituationExchangeSubscriptionRequest Definition	66
7.7.2	SituationExchangeSubscriptionRequest Example	67
7.8	SituationExchangeDelivery	67
7.8.1	ServiceDelivery with a SituationExchangeDelivery	68
7.8.2	SituationExchangeDelivery Element	68
7.8.3	SituationContext Element	68
7.8.4	SituationNetworkContext Element	69
7.8.5	PtSituationElement	69
7.8.6	RoadSituationElement	128
8	SituationExchangeDelivery Examples - SituationExchangeDelivery PT Examples	130
A.1	General	133
A.2	Classes	133
A.3	Enumerations	133
A.4	Groups	133
A.5	Notes	133
A.6	Relationships	133
A.7	Use of Colour	134
A.8	Serialisation: Containment and Reference	134
A.9	Alternative Representations of XML Structures in UML	135
A.10	XML Fragment for Example	137
A.11	Order of Attributes	138
A.12	Direction of Reading	138

A.13	Simple Data Types.....	138
A.14	Reusable Complex Data Types.....	138
B.1	SIRI-SX and Datex2	139
C.1	General.....	142
C.2	Use Cases: Capture and Origination of Situations	142
C.3	CAPT#01 Situations entered manually by operator staff.....	142
C.4	CAPT#02 Situations updated manually by operator staff.....	142
C.5	CAPT#03 Situations being generated automatically from a situation analyser	143
C.6	CAPT#04 Situations arising from Facility Monitoring (e.g. lift failure).....	143
C.7	CAPT#05 Situations arising from Control Actions (e.g. short running, platform change).....	143
C.8	CAPT#06 Situations supplied automatically from a related PT network (e.g. rail incidents being fed to bus system) in both SIRI and TPEG formats	143
C.9	CAPT#07 Situations supplied automatically from a related Road network (e.g. road situations being fed to bus system) Datex2 formats	143
C.10	CAPT#08 Road work affecting bus lanes	143
C.11	CAPT#09 Parking not available at an interchange to PT	143
C.12	CAPT#10 Weather or non-network specific Situation or event.....	144
C.13	CAPT#11 Cross referencing Situations with previous Situations.....	144
C.14	CAPT#12 Workflow for verification, validation and editorial correction.....	144
C.15	CAPT#13 Providing of collective guidance of passengers.....	144
C.16	CAPT#14 Audit trails, retrospectives and process views.....	144
C.17	Use Cases: Relating Situations to other SIRI services.....	144
C.18	XREF#01 Problem affecting a specific vehicle journey	145
C.19	XREF#02 Problem at a stop place affecting some or all journeys for some or all modes	145
C.20	XREF#03 Problem affecting a whole line or a section of a line between two stop places	145
C.21	XREF#04 Problems affecting an interchange.....	145
C.22	XREF#05 Problem affecting a whole network	145
C.23	XREF#06 Disruption (e.g. partial blockage) or degradation (e.g. crowding) of normal travel.....	146
C.24	XREF#07 Problems affecting particular classes of users e.g. impaired mobility.....	146
C.25	Use Cases: Onwards Distribution to other systems (e.g. in TPEG and Datex2).....	146
C.26	DIST#01 Distribution of Situations to displays.....	146
C.27	DIST#02 Distribution of Situations to external information services, e.g. broadcasters	146
C.28	DIST#03 Distribution of Situations to staff.....	146
C.29	DIST#04 Distribution of Situations to alerts and travel angels	147

C.30	DIST#05 Projection of Situations on maps	147
C.31	DIST#06 Distribution of Situations to journey planners	147
C.32	DIST#07 Distribution of Situations to personal navigators and smart devices.....	147
C.33	DIST#08 Distribution of Situations to other incident management systems	147
C.34	DIST#09 Distribution of updates to existing Situations	147
C.35	DIST#10 Aging of Situations and updates.....	148
D.1	Mapping of SIRI-SX elements to GTFS-realtime	149
D.2	Mapping of SIRI-SX Journey Condition to GTFS-realtime ScheduleRelationship	150
D.3	Mapping of SIRI-SX Situation Categories to GTFS-realtime Cause	150
D.4	Mapping of SIRI-SX Service Conditions to GTFS Real-time Effect.....	151
	Bibliography	152

European foreword

This document (CEN/TS 15531-5:2016) has been prepared by Technical Committee CEN/TC 278 “Intelligent transport systems”, the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 15531-5:2011.

The 15531 series consists of the following parts, under the general title *Public transport - Service interface for real-time information relating to public transport operations*

- Part 1: Context and framework
- Part 2: Communications
- Part 3: Functional service interfaces
- Part 4: Functional service interfaces: Facility Monitoring
- Part 5: Functional service interfaces - Situation exchange

The following corrections and modifications have been in this new version of CEN/TS 15531-5:

- Correct spec to include projection attributes for affectedStopPlaceComponent
- Document FacilityRef as part of request
- Document Access Mode as part of request
- Document Scope as part of request
- Document RoadFilter and Accessibility need filter as part of request
- Correct Documentation of AffectedRoads as part of Delivery
- Correct Documentation of capability Matrix
- Correct Documentation of Reason codes
- Added Annex D to Doc on GTFS real-time mapping
- StopMonitoringDelivery upgrade to DatexII

All changes are available in the file ReadMe.txt which is accompanying the XSD-schema, available from <http://www.siri.org.uk>.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta,

Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Public transport services rely increasingly on information systems to ensure reliable, efficient operation and widely accessible, accurate passenger information.

Well-defined, open interfaces have a crucial role in improving the economic and technical viability of Public Transport Information Systems of all kinds. Using standardised interfaces, systems can be implemented as discrete pluggable modules that can be chosen from a wide variety of suppliers in a competitive market, connecting diverse systems; rather than as monolithic proprietary systems from a single supplier. Interfaces also allow the systematic automated testing of each functional module, vital for managing the complexity of increasing large and dynamic systems. Furthermore, with a well-defined, version interface, individual functional modules can be replaced or evolved, without unexpected breakages of obscurely dependent function.

The SIRI framework is a European Technical Specification that provides a specification for a number of functional interfaces that allow public transport data of specific types to be exchanged readily using structured interfaces.

This further Technical Specification specifies an additional SIRI functional service to exchange incident and event information about disruptions to public transport between servers containing real-time public transport vehicle or journey time data. These include the control centres of transport operators as well as information systems that deliver passenger travel information services.

This document describes the SIRI Situation Exchange service, one of a modular set of services for the exchange of Real-time information. The Situation Exchange service (SIRI-SX) is concerned with the exchange of planned events and unplanned incident data among systems, including incident capture, real-time management and dissemination systems. It is an additional functional service based on the European Technical Specification known as “SIRI” – Service Interface for Real-time Information. SIRI provides a framework for specifying communications and data exchange protocols for organisations wishing to exchange Real-time Information (RTI) relating to public transport operations.

The specification for the base SIRI framework on which SIRI-SX is built is presented in three parts:

- a) context and framework, including background, scope and role, normative references, terms and definitions, symbols and abbreviations, business context and use cases (SIRI Part 1: EN 15531-1);
- b) the mechanisms to be adopted for data exchange communications links (SIRI Part 2: EN 15531-2);
- c) data structures for a series of individual application interface modules (SIRI Part 3: EN 15531-3):
 - 1) Production Timetable (SIRI-PT);
 - 2) Estimated Timetable (SIRI-ET);
 - 3) Stop Timetable (SIRI-ST);
 - 4) Stop Monitoring (SIRI-SM);
 - 5) Vehicle Monitoring (SIRI-VM);
 - 6) Connection Timetable (SIRI-CT);
 - 7) Connection Monitoring (SIRI-CM);
 - 8) General Message (SIRI-GM).

Additional documents are used for additional functional services, to date these are:

- **Facilities Management (SIRI-FM)** service is used to exchange information on the current status of facilities such as lifts, escalators or ticketing machines. It provides a short description of the facility itself, expresses any change to its operational status and specifically the accessibility status for the disabled or those with special needs people. It provides all the current relevant information relating to all facilities fulfilling a set of selection criteria (Part 4: CEN/TS 15531-4).
- **Situation Exchange (SIRI-SX)**: this document. The SIRI Situation and Incident Exchange service is used to exchange information messages between identified participants in a standardised structured format suitable for travel information services. It enables messages to be sent and to be revoked (Part 5: CEN/TS 15531-5, this document).

The XML schema can be downloaded from <http://www.siri.org.uk/>, along with available guidance on its use, example XML files, and case studies of national and local deployments. The SIRI-SX service is included in version 1.3 of the schema onwards.

1 Scope

The SIRI Situation Exchange service (SIRI-SX) allows the efficient exchange of data about Situations caused by planned and unplanned incidents and events and is intended to support the use cases identified in Annex C. Situations are actual or potential perturbations to normal operation of a transport network. The SIRI-SX service uses the common SIRI communication framework and services which are described in EN 15531-1 and EN 15531-2 and not repeated in this document.

The Situation Exchange service has a rich Situation model, allowing a structured description of all aspects of multimodal travel Situations, including cause, scope, effect and rules for distribution to an audience. The structured values enabling computer based distribution through a wide variety of channels, and the presentation of data in different formats for different device and different audiences. The Situation Exchange Service allows the exchange of incident and event information between, amongst others:

- Control centres;
- Operations Staff;
- Public Information systems;
- Alert systems and personalised alert systems;
- UTM systems;
- Journey planners;
- AVMS (Automatic Vehicle Management Systems).

SIRI-SX uses a network model based on the CEN Transmodel conceptual model for Public Transport networks, schedules and operations, along with the CEN Identification of Fixed Objects in Public Transport (IFOPT) model for describing physical transport interchanges.

The Situation Exchange service is envisaged as a 'back office' capture and exchange service that will feed other public facing travel information dissemination systems in particular those using the TPEG format. Transport Protocol Expert Group (TPEG) is a European Broadcasting Union fostered standard for broadcasting travel data over Digital Assisted Broadcasting (DAB) radio and other channels. TPEG is maintained by the Traveller Information Services Association (TISA). To this end, the SIRI-SX situation classification model has been harmonized as far as possible with that of TPEG and DATEX2 so that full interoperability can be achieved. Uses of structured elements from TPEG, for which translations already exist in most European languages, also facilitates human readability in different national languages. Maintaining and improving a harmonization with TPEG will be a continuing objective. In addition to the TPEG exchangeable content, SIRI-SX messages contain additional structured information which allows them to be processed in additional ways.

Situation and computer systems and applications are typically *distributed*, that is information will be captured on one system and exchanged with others for dissemination and further processing. This means that a message design is needed that allows the management of the identity of distributed messages over time and across different systems, so that subsequent updates to a Situation can be reconciled by different systems over a network, and obsolete messages can be retired automatically. The SIRI-SX SITUATION model is designed to support the distributed management of Situations.