

BSI Standards Publication

Fibre optic communication system design guides

Part 15: Cable plant and link – Testing multi-fibre optic cable plant terminated with MPO connectors



National foreword

This British Standard is the UK implementation of IEC TR 61282-15:2017.

The UK participation in its preparation was entrusted to Technical Committee GEL/86/3, Fibre optic systems and active devices.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017 Published by BSI Standards Limited 2017

ISBN 978 0 580 94670 7

ICS 33.180.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2017.

Amendments/corrigenda issued since publication

Date Text affected



IEC TR 61282-15

Edition 1.0 2017-05

TECHNICAL REPORT

Fibre optic communication system design guides – Part 15: Cable plant and link – Testing multi-fibre optic cable plant terminated with MPO connectors





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC TR 61282-15

Edition 1.0 2017-05

TECHNICAL REPORT

Fibre optic communication system design guides –
Part 15: Cable plant and link – Testing multi-fibre optic cable plant terminated with MPO connectors

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.180.01 ISBN 978-2-8322-4238-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| F | DREWO | RD | 4 |
|----|---------|---|------------|
| IN | TRODU | CTION | 6 |
| 1 | Scop | e | 7 |
| 2 | Norm | ative references | 7 |
| 3 | Term | s, definitions and abbreviated terms | 7 |
| | 3.1 | Terms and definitions | 7 |
| | 3.2 | Abbreviated terms | |
| 4 | MPO | connectors | |
| | 4.1 | General | 9 |
| | 4.2 | Keying and fibre positions | |
| | 4.3 | Polarity | |
| 5 | Test | methods and measurements | |
| | 5.1 | General | 12 |
| | 5.2 | Attenuation | |
| | 5.3 | Polarity | |
| | 5.4 | Length | |
| | 5.5 | Optical return loss and reflectance | 12 |
| 6 | Varia | tions of test methods | 13 |
| | 6.1 | General | 13 |
| | 6.2 | Optical light source | 13 |
| | 6.2.1 | General | 13 |
| | 6.2.2 | Source with MPO interface | 13 |
| | 6.2.3 | Source with non-MPO interface and fan-out cable | 14 |
| | 6.2.4 | Source with non-MPO interface and optical switch | 14 |
| | 6.3 | Optical power meter | 14 |
| | 6.3.1 | General | 14 |
| | 6.3.2 | Meter with MPO interface having multiple detectors | 14 |
| | 6.3.3 | Meter with MPO interface having large area detector | 15 |
| | 6.3.4 | Meter with non-MPO interface and fan-out cable | 15 |
| | 6.3.5 | 1 | |
| | 6.4 | OTDR | |
| | 6.4.1 | General | |
| | 6.4.2 | | |
| | 6.4.3 | | |
| | 6.4.4 | ' | |
| | 6.5 | Other adaptations and accessories | |
| | 6.5.1 | Adapters | |
| | 6.5.2 | | |
| | 6.5.3 | ' | |
| | 6.5.4 | , , , | |
| 7 | 6.6 | Visual inspectionconfigurations | |
| 7 | | | |
| | 7.1 | General LSDM with MDO interface | |
| | 7.2 | LSPM with NPO interface and for outs | |
| D: | 7.3 | LSPM with non-MPO interface and fan-outs | |
| DI | nnograp | hy | ∠ I |

IEC TR 61282-15:2017 © IEC 2017 - 3 -

| Figure 1 – MPO connector | <u></u> |
|--|---------|
| Figure 2 – Polarity for three standard configurations | |
| Figure 3 – Polarity for a breakout cord | 11 |
| Figure 4 – Reference connections for cabling with unpinned MPO plugs | 18 |
| Figure 5 – Connections for measurements on type A cabling with unpinned MPO connectors | 18 |
| Figure 6 – Reference connections for tester with non-MPO plugs | 19 |
| Figure 7 – Connections for tester with non-MPO plugs | 20 |

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

Part 15: Cable plant and link – Testing multi-fibre optic cable plant terminated with MPO connectors

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 61282-15, which is a Technical Report, has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

The text of this Technical Report is based on the following documents:

| Enquiry draft | Report on voting |
|---------------|------------------|
| 86C/1427/DTR | 86C/1443/RVDTR |

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

IEC TR 61282-15:2017 © IEC 2017

- 5 -

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61282 series, published under the general title *Fibre optic communication system design guides*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

- 6 **-**

Cabling testing standards such as IEC 61280-4-1 for multimode attenuation measurements and IEC 61280-4-2 for single-mode attenuation and optical return loss measurement describe testing simplex or duplex fibre cabling terminated with single-fibre ferrule connectors (e.g. LC). This document has been written to describe measurement methods for attenuation and polarity and can be used in the absence of any multi-fibre testing standard.

This document addresses the testing of installed multimode and single-mode cabling terminated with multi-fibre connectors of IEC 61754-7 (all parts) related to multi-fibre push on (MPO) and describes the challenges when testing array connectivity, which parameters are important to measure, and why the test methods of IEC 61280-4-2 and IEC 61280-4-1 cannot be used.

Installed optical fibre cabling terminated with MPO interfaces can be tested in different ways, for example, with equipment having an MPO connector test port. Testing using other types of equipment is possible, for example using an optical time domain reflectometer (OTDR).

This document focuses on MPO connectors containing 12 fibres in a single row; however, many of the principles can also be applied to testing of cabling terminated with different types of MPO connectors with appropriate changes to test cords and/or test equipment interfaces.

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES -

Part 15: Cable plant and link – Testing multi-fibre optic cable plant terminated with MPO connectors

1 Scope

This part of IEC 61282 provides guidance for the testing of multi-fibre cable, multimode or single-mode, terminated with plugs described in IEC 61754-7 (all parts) (multiple-fibre push on – MPO). Guidance is provided on the measurement of attenuation, polarity, length and optical return loss. The cabling can be installed in a variety of environments, including residential, commercial, industrial, and data centre premises, and possibly in outside plant environments.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61280-4-1, Fibre-optic communication subsystem test procedures – Part 4-1: Installed cable plant – Multimode attenuation measurement

IEC 61280-4-2, Fibre-optic communication subsystem test procedures – Part 4-2: Installed cable plant – Single-mode attenuation and optical return loss measurement

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1.1

adapter

part of a connector in which one or two plugs are inserted and aligned

3.1.2

attenuation

reduction of optical power induced by transmission through a medium such as cabling, given as

$$L = 10 \log_{10}(P_{in}/P_{out})$$

where $P_{\rm in}$ and $P_{\rm out}$ are the power, typically measured in mW, into and out of the cabling

Note 1 to entry: Attenuation is expressed in dB.