



BSI Standards Publication

Metallic materials — Principles and designs for multiaxial fatigue testing

National foreword

This Published Document is the UK implementation of ISO/TR 12112:2018.

The UK participation in its preparation was entrusted to Technical Committee ISE/101/6, Fatigue testing of metals and metal matrix composites.

The UK committee would like to clarify the relationship between the images and keys in the figures of Annex A. The images correspond with their position in the key, with the left column containing images 1, 2, and 3 in ascending order, and the right column containing images 4, 5, and 6 in ascending order. This applies to both Figures A.1 and A.2.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 539 01063 3

ICS 77.040.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2018.

Amendments/corrigenda issued since publication

Date	Text affected
31 May 2018	Missing elements of Figures A.1 and A.2 reinstated

Metallic materials — Principles and designs for multiaxial fatigue testing

Matériaux métalliques — Principes et conceptions associés aux essais de fatigue multiaxiale





COPYRIGHT PROTECTED DOCUMENT

© ISO 2018, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General principles	2
4.1 Methodology	2
4.2 Historical development	2
4.3 Specific multiaxial test methods	6
4.3.1 Bending + torsion[6]	6
4.3.2 Axial + torsion[7]	6
4.3.3 Axial + internal pressure[8]	6
4.3.4 Axial + internal + external pressure[9]	6
4.3.5 Axial + internal + external pressure + torsion[10]	6
4.3.6 Cruciform — LCF[11]	6
4.3.7 Cruciform — Crack growth[12]	7
4.4 Multiaxial fatigue analysis	7
4.4.1 Computer aided design	7
4.4.2 Fatigue life prediction	7
4.5 Multiaxial fatigue failure criteria	8
5 Axial + torsion testing systems and specimen design	8
5.1 Historical development	8
5.2 Specimen design	10
5.2.1 Design considerations	10
5.2.2 Design recommendations	10
5.2.3 Comparison with ASTM E2207[4]	10
5.3 Machine design	11
5.3.1 Frame	11
5.3.2 Loadcells	11
5.3.3 Strain measurement	11
5.3.4 Control	11
5.3.5 Data acquisition	11
5.3.6 Software	11
6 Cruciform testing systems and specimen design	12
6.1 Historical development	12
6.2 Specimen design	12
6.3 Machine design	13
6.3.1 Frame	13
6.3.2 Loadcells	13
6.3.3 Strain measurement	14
6.3.4 Crack growth monitoring	14
6.3.5 Control	14
6.3.6 Data acquisition	14
6.3.7 Software	14
7 Axial + differential pressure systems and specimen design	15
7.1 Historical development	15
7.2 Specimen design	18
7.2.1 Design considerations	18
7.2.2 Design recommendations	18
7.2.3 Axial stress due to pressure	19
7.3 Machine design	19
7.3.1 Frame	19

7.3.2	Pressure containment.....	19
7.3.3	Differential pressure.....	19
7.3.4	Force measurement.....	19
7.3.5	Pressure measurement.....	19
7.3.6	Strain measurement.....	19
7.3.7	Control.....	19
7.3.8	Data acquisition.....	19
7.3.9	Software.....	20
Annex A Historical analysis of specimen geometry.....		21
Bibliography		28

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 164, *Mechanical testing of metals*, Subcommittee SC 4, *Fatigue, fracture and toughness testing*.

Introduction

Structural components in industry are frequently subject to some form of multiaxial stressing. Fatigue cracks generally initiate from surface defects or discontinuities and are thus primarily influenced by the surface biaxial stress system. This can vary from equibiaxial, where surface principal stresses are equal in magnitude and sign (present under conditions of pressurization, rotation and thermal loading) to pure shear where surface stresses are equal in magnitude, opposite in sign (as in shafts and shear panels).

The majority of fatigue test data gathered worldwide have been and will continue to be under uniaxial conditions for reasons of simplicity and cost. A secondary goal of multiaxial testing is therefore to develop behavioural models which relate failure under specified multiaxial conditions to established uniaxial cases.

This document utilizes data gathered from the past 80 years spanning most multiaxial fatigue research. It can be of interest to new researchers in the field and form a basis for full International Standards as the need arises.

Metallic materials — Principles and designs for multiaxial fatigue testing

1 Scope

This document discusses the general principles of multiaxial fatigue testing and the design recommendations for specific classes of multiaxial testing machines and test specimens.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

biaxial strain ratio

ϕ

ratio of the surface principal strains, smaller/larger

3.2

biaxial stress ratio

ψ

ratio of the surface principal stresses, smaller/larger

3.3

principal strains

$\varepsilon_1 > \varepsilon_2 > \varepsilon_3$

principal direct strains at a point in a multiaxial strain field

3.4

principal stresses

$\sigma_1 > \sigma_2 > \sigma_3$

principal direct stresses at a point in a multiaxial strain field

3.5

Poisson's ratio

ν

negative ratio of transverse to longitudinal strain under uniaxial tensile stressing

3.6

specimen diameter

d

diameter of a cylindrical tubular specimen

Note 1 to entry: The symbols d_0 , d_i and d_m are used to express outside, inside and mean diameters, respectively.