PD ISO/TS 19709-2:2016

BSI Standards Publication

Transport packaging — Small load container systems

Part 2: Column Stackable System (CSS)

bsi.

...making excellence a habit.™

National foreword

This Published Document is the UK implementation of ISO/TS 19709-2:2016.

The UK participation in its preparation was entrusted to Technical Committee PKW/0, Packaging.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Published by BSI Standards Limited 2016

ISBN 978 0 580 88218 0

ICS 55.020

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 February 2016.

Amendments/corrigenda issued since publication

Date	Text affected

PD ISO/TS 19709-2:2016

TECHNICAL SPECIFICATION

ISO/TS 19709-2

First edition
2016-02-01

Transport packaging — Small load container systems —

Part 2: Column Stackable System (CSS)

Emballage — Systèmes de transport de petites charges —

Partie 2: Systèmes gerbable en colonnes (SGP)

Reference number
ISO/TS 19709-2:2016(E)

COPYRIGHT PROTECTED DOCUMENT

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 122, *Packaging*.

ISO 19709 consists of the following parts, under the general title *Transport packaging — Small load container systems*:

— *Part 1: Common requirements and test methods*

— *Part 2: Column Stackable System (CSS)* [Technical Specification]

— *Part 3: Bond Stackable System (BSS)* [Technical Specification]

Introduction

The small load container (SLC) system specified in this part of ISO 19709 was first conceived for handling, storage and transport of goods and designed to meet the needs of automotives manufacturers and their suppliers.

The multi-functional design of its elements allow a SLC system manufactured in accordance with ISO 19709 to meet the requirements of different manual, mechanical and automatic handling, transport and storage systems in the automotive industry transportation chain. It is likely that this system of SLCs and accessories will frequently be used in a pool.

The special characteristic of the system specified in ISO 19709 is the self-securing mechanism of the unit load in the column stack. For this reason, this system is called column stackable system.

The CS system consists of the following elements:

— CSS-SLC;

— Lid [the prefix “D” reflects the German term for “lid” (Deckel)];

— Pallet cover [the prefix “A” reflects the German term for “cover” (Abdeckung)].

The use of CSS-SLC systems with palletized loads is discussed in Annex A.

Transport packaging — Small load container systems —

Part 2: Column Stackable System (CSS)

1 Scope

This part of ISO 19709 specifies the main characteristics and the testing of durable, reusable, parallelepipedic containers and their accessories which form a column stackable system (CSS) designed to contain bulk or precisely located component loads up to maximum load of 20 kg used for automotive industry applications.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19709-1:—[1)], *Transport packaging — Small load container systems — Part 1: Common requirements and test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19709-1 and the following apply.

3.1
CSS small load container
small load container (SLC) with special functional features which ensure a mutual compatibility

3.2
pallet cover
system element with a safeguarding and protective function that closes the top of the loading unit with a level surface that distributes the mass of overlying loads in a stack

3.3
SLC capacity
usable inner volume which is calculated by multiplying the usable inner length by the usable inner width (both measured at half height) and the usable inner height

3.4
SLC lid (D 65, D 45, D 35)
BSS-SLC and CSS-SLC system elements with virtually neutral height for protection of the cargo

Note 1 to entry: The prefix “D” reflects the German term for “lid” (Deckel).

Note 2 to entry: The number 65 means lid for the 600 mm × 400 mm size containers. The number 45 means lid for the 400 mm × 300 mm size containers. The number 35 means lid for the 300 mm × 200 mm size containers.

3.5
SLC unit load
load consisting of a SLC which forms a unit for handling, transport, stacking and storage

1) To be published.