

BSI Standards Publication

Ambient air — Determination of the mass concentration of tire and road wear particles (TRWP) — Pyrolysis-GC-MS method



National foreword

This Published Document is the UK implementation of ISO/TS 20593:2017.

The UK participation in its preparation was entrusted to Technical Committee EH/2/3, Ambient atmospheres.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017 Published by BSI Standards Limited 2017

ISBN 978 0 580 90887 3

ICS 13.040.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2017.

Amendments/corrigenda issued since publication

Date Text affected

PD ISO/TS 20593:2017

TECHNICAL SPECIFICATION

ISO/TS 20593

First edition 2017-06

Ambient air — Determination of the mass concentration of tire and road wear particles (TRWP) — Pyrolysis-GC-MS method

Air ambiant — Détermination de la concentration en masse de particules provenant de l'usure des pneumatiques et des chaussées (TRWP) — Méthode par pyrolyse-CG/SM



PD ISO/TS 20593:2017 **ISO/TS 20593:2017(E)**



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents		Page
Fore	eword	V
Intro	oduction	vi
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Symbols and abbreviated terms	
-	4.1 Symbols of units (see also ISO 4226)	3
5	Principle	4
6	Reagents	5
7	Apparatus 7.1 Air sampling — Equipment and consumable supplies 7.2 Specimen preparation laboratories 7.3 Equipment for analysis 7.4 Consumables	
8	Measuring range	7
9	Limit of detection	7
10	Procedure 10.1 General 10.2 Sample collection 10.3 Deuterated internal standard preparation 10.4 Calibration curve preparation 10.4.1 Stock solutions 10.4.2 Calibration curves 10.5 Sample preparation 10.5.1 Filter conditioning 10.5.2 Total PM _{2,5} and PM ₁₀ 10.5.3 Filter preparation 10.5.4 Internal standard addition 10.6 Sample pyrolysis 10.7 Sample measurement	77 88 88 89 99 10 10 10 10 10
11	Analysis 11.1 General 11.2 Total PM _{2,5} or PM ₁₀ concentration 11.3 TRWP detection limit 11.4 Quantity of tyre polymer in the sample 11.5 Air concentration of TRWP 11.6 Mass concentration of TRWP	
12	Performance characteristics	
	12.1 General 12.2 Specific performance characteristics 12.3 Method detection limit	12
13	Test report	12
Anne	nex A (informative) Recipe for calibration curves and stock solutions	14
Anne	nex B (informative) Curie-point pyrolyser	16
	nex C (informative) Representative calibration curves and pyrograms	
	nex D (normative) Calculation of TRWP detection limits	2.4

PD ISO/TS 20593:2017 **ISO/TS 20593:2017(E)**

Annex E (normative) Calculation of results using dimer markers	26
Bibliography	28

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 146, *Air quality*, Subcommittee SC 3, *Ambient atmospheres*.

Introduction

Tyre and road wear particles (TRWP) are formed as a result of tread abrasion from the road surface and subsequent particle release to the environment. TRWP consist of tyre tread particles which include incorporated material from the road surface. The elastomeric fraction in TRWP contained in $PM_{2,5}$ or PM_{10} is quantified in this document by direct pyrolysis-GC-MS analysis of a sample filter. Mass can be expressed on the basis of the rubber polymer, tyre tread, or TRWP. This method has been used to measure the airborne concentration of TRWP in the PM_{10} fraction for three geographically separated regions. The TRWP concentration in soil and sediment has also been characterized by a similar method.

Specific chemical markers are generated from intact TRWP by pyrolysis of sample specimens. The chemical markers consist of characteristic and specific pyrolysis dimeric fragments of passenger and truck tyre tread polymers including butadiene rubber, styrene-butadiene rubber, and isoprene rubber. The polymer fragments generated by sample pyrolysis are subsequently separated by gas chromatography and identified by mass spectroscopy. The TRWP mass concentration is calculated based on market average polymer use rates in tread and prior characterization of the mineral content of TRWP. Rubber polymer specificity is achieved by quantification of dimeric polymer fragments consisting of two monomer units. [6][7] Repeatability is achieved by the use of a deuterated internal standard of similar polymeric structure to the tyre tread polymers. The internal standard corrects for variable analyte recovery caused by sample size, matrix effects, and temporal variation in instrument response. The method is suitable for monitoring changes in ambient air TRWP concentrations over a specified averaging time.

Ambient air — Determination of the mass concentration of tire and road wear particles (TRWP) — Pyrolysis-GC-MS method

WARNING 1 — Persons using this document should be familiar with normal laboratory practice. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any national regulatory conditions.

WARNING 2 — Certain procedures specified in this document may involve the use or generation of substances, or the generation of waste, that could constitute a local environmental hazard. Reference should be made to appropriate documentation on safe handling and disposal after use.

1 Scope

This document specifies a method for the determination of the airborne concentration ($\mu g/m^3$), mass concentration ($\mu g/g$) and mass fraction (%) of tyre and road wear particles (TRWP) in ambient particulate matter (PM) samples.

This document establishes principles for air sample collection, the generation of pyrolysis fragments from the sample, and the quantification of the generated polymer fragments. The quantified polymer mass is used to calculate the fraction of tyre tread in PM and concentration of tyre tread in air. These quantities are expressed on a TRWP basis, which includes the mass of tyre tread and mass of road wear encrustations, and can also be expressed on a tyre rubber polymer or tyre tread basis.

Air sample collection is on quartz fibre filters with size-selective input in a range of $PM_{2,5}$ or PM_{10} . The method is suitable for the determination of TRWP in indoor or outdoor atmospheres.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4225, Air quality — General aspects — Vocabulary

ISO 7708:1995, Air quality — Particle size fraction definitions for health-related sampling

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4225 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

ambient air

outdoor air to which people, plants, animals, or material may be exposed