



BSI Standards Publication

Road vehicles — Displacement calibration method of IR-TRACC devices

National foreword

This Published Document is the UK implementation of ISO/TS 21476:2018.

The UK participation in its preparation was entrusted to Technical Committee AUE/7, Automobile occupant restraint systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018

Published by BSI Standards Limited 2018

ISBN 978 0 580 93905 1

ICS 43.020

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 December 2018.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL SPECIFICATION

**ISO/TS
21476**

First edition
2018-12-15

Road vehicles — Displacement calibration method of IR- TRACC devices

*Véhicules routiers — Méthode d'étalonnage de déplacement des
dispositifs IR-TRACC*



Reference number
ISO/TS 21476:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	3
5 Displacement Calibration Procedure	5
5.1 Preparations	5
5.2 Test equipment set-up, power supply, voltmeter	6
5.3 Establish starting point	6
5.4 Forced Lateral Manipulation Test	7
5.5 Displacement Calibration Data Collection	8
5.6 Parameter optimization and data review	9
6 Displacement Calibration Data Processing	10
6.1 General	10
6.2 Linearization over calibration range with nominal exponent	10
6.3 Linearization optimization	10
6.4 Data analysis and pass criteria calculations	11
6.4.1 Optimized Nominal Linearity Error	11
6.4.2 Tubes In-Out Variation	11
6.4.3 Pass-fail tests and limits	12
6.4.4 Forced Lateral Manipulation variation	12
6.5 Example Data	12
Annex A (informative) Sensor Model Numbers	14
Annex B (informative) Example Calibration Template	15
Bibliography	19

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 36, *Anthropomorphic test devices*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document was written to address the need of the automotive crash testing community for a well-defined calibration method of non-linear telescopic displacement sensors known as IR-TRACC. This device is commonly used on crash dummies to measure the chest deflection as injury an assessment parameter. Various aspects specific to this type of sensors are addressed in this procedure, among others linearization of the exponential voltage output and the sensitivity to tubes position of the telescopic devices.

Road vehicles — Displacement calibration method of IR-TRACC devices

1 Scope

This document establishes a procedure to calibrate IR-TRACC displacement transducers. Like all other sensors used on dummies, calibration is required. The calibration is carried out with the sensor disassembled from the dummy. The procedure is valid for sensors with analogue as well as digital output.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6487, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

IR-TRACC

Infra-Red Telescoping Rod for the Assessment of Chest Compression

non-ratiometric displacement transducer used to measure chest deflection in crash dummies

Note 1 to entry: The technology of the transducer was described in a paper by Rouhana et al. [1998]^[1]. The measurement principle is based on emission of infra-red light by an LED and a phototransistor sensitive to irradiance. The transducer is a non-linear device, as the irradiance and output voltage is proportional to the inverse square of the distance between the emitter and the phototransistor. The distance between the phototransistor and the LED is theoretically proportional to the inverse square root of the phototransistor output voltage: $d = C/\sqrt{U_{IR}}$. The inverse square root of the output voltage can also be written as the output voltage to the power of minus 0,5, therefore $d = C \times U_{IR}^{-0,5}$

3.2

Displacement Calibration

classic compression method where the zero mm starting point is defined close to the extended range of the sensor

Note 1 to entry: When the IR-TRACC overall length decreases (IR-TRACC compresses), its calibrated mm output increases. The IR-TRACC linearized output is negatively proportional to its length. During displacement calibration components are used to fix the transducer to a calibration fixture. These components do not necessarily belong to the final assembly of the sensor as used in the dummy. The displacement calibration therefore is not an absolute point to point (distance) calibration against a fixed reference. This is not necessary as the chest deflection of the dummy is calculated with respect to the IR-TRACC displacement at time zero. The IR-TRACC displacement output is associated with the ISO MME^[2] Code **DS** for **Displacement**.